

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-31181

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, New Mexico 88210

4. Well Location

Unit Letter P : 330 Feet From The South Line and 990 Feet From The East Line

Section

20

Township

13S

Range

34E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4157' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Intermediate & Production Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11" hole 4-4-91. Ran 100 jts 8-5/8" S-80 and J-55 casing set at 4248'. Guide shoe set 4248', float collar set 4201'. Cemented w/1550 sx Howco Lite "C" w/1/4#/sx Flocele + 8#/sx Salt. Tailed in w/200 sx "C" + 2% CaCl. PD 10:45 PM 4-4-91. Bumped plug to 1550 psi, released pressure, float held OK. Circulated 175 sacks to pit. WOC. Drilled out 7:15 PM 4-5-91. WOC 20 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

TD 10981'. Reached TD 4-29-91. Ran 255 jts 5-1/2" 17# and 20# N-80 LT&C casing set 10981'. Float shoe set 10981', float collar set at 10933'. Cemented w/1000 gals Superflush 101, 750 sx Halliburton "H" with 5# KCL + .6 Halad 22A + .3% of CFR-3 (yield 1.20, wt 15.7). PD 4:15 PM 5-3-91. Cement did not circulate. Bumped plug to 2000 psi for 3 mins. float and casing held OK. WOC 18 hrs. WOCU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Juanita Goodlett

TITLE

Production Supervisor

DATE 5-7-91

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: