

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31648
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG 2265

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Superior WA State
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 5
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Saunders Permo Upper Penn
4. Well Location Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line Section 11 Township 14S Range 33E NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4195' GR

1. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17½" starter hole 9:30 AM 7-18-92. Resumed drilling 17½" hole 9:00 PM 7-20-92. Ran 11 joints 13-3/8" 54.5# casing set 470'. Guide shoe set 470'. Insert float set 427'. Cemented w/525 sx Class "C" + 2% caCl2 (yield 1.32, wt 14.8). PD 11:00 aM 7-21-92. Bumped plug to 500 psi, float held OK. Circulated 115 sacks cement. WOC. Drilled out at 5:00 AM 7-22-92. WOC 18 hours. Cut off and weld on flow nipple. Reduced hole to 11" and resumed drilling. Notified NMOCD, Hobbs, NM, to witness. No witnesses.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 7-23-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JUL 27 '92

RECEIVED

JUL 24 1992

OCD HOBBS OFFICE