

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32188
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Childress AKV
8. Well No. 1
9. Pool name or Wildcat Saunders Permo Upper Penn

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Well Location Unit Letter M : 990 Feet From The South Line and 330 Feet From The West Line Section 1 Township 14S Range 33E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4184' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Set Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
TD 12-1/4" hole 6:15 PM 11-24-93. Ran 93 joints 9-5/8" casing set at 4130' as follows:  
23 joints 9-5/8" 40# J-55 LT&C, 68 joints 9-5/8" 36# J-55 ST&C, 2 joints 9-5/8" 39# J-55 ST&C.  
Regular guide shoe set 4130', float collar set 4082'. Cemented with 200 sx PSL "C" with 1/2# Celloseal + 5# Gilsonite + 5# Salt (yield 12.7, wt 1.97) and 1100 sx PSL "C" with 1/2# Celloseal + 5# Salt (yield 1.97, wt 12.4). Tailed in w/200 sx "C" with 2% CaCl2 (yield 1.32, wt 14.8). PD 9:15 AM 11-25-93. Bumped plug to 2000 psi, held OK. Circulated 140 sacks. WOC. NU and tested to 3000 psi for 10 minutes. Drilled out 3:45 AM 11-26-93. WOC 18 hours and 30 minute. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-2-93  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

**ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR**

**DEC 06 1993**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: