

PAGE START DATE: 7/17/95
PAGE START TIME: 14:41: 0
DATA FILE: 10

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	6000.00	121.00	
0.150	6440.00	124.00	
0.167	6500.00	127.00	BREAK
0.233	6659.00	124.50	
0.267	6757.00	128.25	
0.300	6860.00	127.25	
0.417	7250.00	131.00	
0.450	7369.00	127.50	
0.517	7607.00	131.25	
0.583	7852.00	130.00	
0.600	7914.00	132.25	
0.633	8041.00	131.50	
0.650	8104.00	133.00	
0.667	8168.00	132.50	
0.700	8294.00	134.75	
0.733	8424.00	133.75	
0.767	8572.00	136.50	
0.833	8923.00	146.50	
0.883	9084.00	145.50	
0.933	9247.00	147.75	
0.950	9300.00	147.00	
0.983	9398.00	151.75	
1.000	9443.00	148.25	
1.017	9489.00	149.25	
1.033	9532.00	147.75	
1.067	9635.00	167.00	
1.100	9720.00	157.75	
1.117	9758.00	167.50	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

JULY 17, 1995 @ 3:35 AM

DATE AND TIME SURVEY MADE:

JULY 17, 1995 @ 3:35 PM

AMOUNT AND TYPE OF CEMENT USED:

400 SACKS PREMIUM 50:50 POSMIX, 3# KCL,
6/10% HALIDE 9 RUN THROUGH D.V. TOOL
AT 9882 FEET, BEHIND 5½" CASING IN A
7-7/8" HOLE.

DEPTH FIGURED FROM:

KELLY BUSHING

