

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-32860

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. BOX 832, MIDLAND, TX 79702

4. Well Location
Unit Letter **B** : **350** Feet From The **NORTH** Line and **1550** Feet From The **EAST** Line
Section **20** Township **13S** Range **38E** NMPM **LEA** County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3827' GR

7. Lease Name or Unit Agreement Name

LOWE 20

8. Well No.
1

9. Pool name or Wildcat
WILDCAT (DEVONIAN)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

05/25/95 40' of 20" CONDUCTOR SET & CEMENT TO SURFACE.

05/26/95 SPUD WELL AT 7:45AM MST 05/26/95. DRLD SURFACE HOLE TO 567'. RU & RUN 13 JTS 13-3/8" 54.50# CSG. SET @ 567'. CEMENT 13-3/8" CSG W/650 SXS CLASS "C" CEMENT W/2% CACL₂. CEMENT CIRC. TO SURFACE. WOC.

05/28/95 CUT OFF 13-3/8" CSG & WELD ON BRADENHEAD. NU BOP & TEST TO 500 PSI, OK. DRLD FLOAT & CEMENT.

06/03/95 WASH TO BTM W/15 JTS 8-5/8" 32# HC K-55 CSG + 89 JTS 8-5/8" 32# K-55 CSG. 4630' TOTAL. SET @ 4624'. CEMENT 8-5/8" CSG W/900 SXS HOWCO LITE, 15# SALT, 1/4# FLOCELE. TAIL W/250 SXS CLASS "C" CEMENT W/2% CACL₂. CEMENT CIRC. TO SURFACE. SET SLIPS & CUT OFF 8-5/8" CSG. NU WELLHEAD & BOP & TEST TO 1500 PSI, OK. DRLD FLOAT & CEMENT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE **REGULATORY ANALYST** DATE **JUNE 6, 1995**

TYPE OR PRINT NAME **DOROTHEA LOGAN**

TELEPHONE NO. **915 684-7441**

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

JUN 08 1995

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

100-30-100

RECEIVED
JUN 17 1895
U.S. DEPT. OF JUSTICE
OFFICE