

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address. SULLIVAN & COMPANY 3D PROGRAM I L.L.C. 3031 1st PLACE TOWER 15 EAST 5th STREET TULSA, OKLAHOMA 74103-4331 ATT: MARC GARRETT		OGRID Number 146951
		API Number 30-025-33002
Property Code 19210	Property Name LOWE "25"	Well No. 1

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D E	25	13S	37E		2105'	North	60'	West	Lea

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D E	25	13S	37E		2205'	North	100'	West	Lea
Proposed Pool 1 King-Devonian 35910					Proposed Pool 2				

Work Type Code N	Well Type Code O	Cable/Rotary R	Lease Type Code P	Ground Level Elevation 3859
Multiple	Proposed Depth 12600'	Formation Devonian	Contractor NORTON	Spud Date 6/28/95

21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2"	13 3/8"	48#	400	425 Sx. "C"	Circulate
12 1/4"	8 5/8"	32#	4650'	1190 Sx. "C"	Circulate
7 7/8"	5 1/2"	17 & 20#	12600'	235 Sx. "H"	

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 17 1/2" hole to 400' run and set 400' of 13 3/8" H-40 48# ST&C csg. Cement with 425 Sx. Class "C" plus additives, circulate cement to surface.
2. Drill 12 1/4" hole to 4650' run and set 4650' of 8 5/8" J-55 32# ST&C csg. Cement with 940 Sx. Class "C" light cement plus additives tail in with 250 Sx. Class "C" plus additives. Circulate cement to surface.
3. Drill 7 7/8" hole to 12600' run and set 12600' of 5 1/2" N-80 17 & 20 # LT&C and Butt. csg. Cement with 235 Sx. Class "H" cement plus additives. Top cement 12000'

23 I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Joe T. Janica*
Printed name: Joe T. Janica
Title: Agent
Date: 06/14/95
Phone: 392-2112

OIL CONSERVATION DIVISION

Approved by: *Orig. Signed by Paul Knuts*
Title: Geologist
Approval Date: JUN 27 1995
Expiration Date:
Conditions of Approval:
Attached ☒

Approval to begin drilling -- CANNOT produce until Non-Standard Location is approved.

RECEIVED

SEP 14 1995
JUD HUBBS
OFFICE