

LOWE 20, WELL #2
WELL COMPLETION REPORT
MARCH 22, 1996
PAGE 2

ITEM #26: PERFORATION RECORD (INTERVAL, SIZE, & NUMBER)

4 JSPF @ 9898 - 9912', 9922 - 9928'.

4 JSPF @ 9724 - 9827', 9733 - 9740', 9808 - 9810', 9824 - 9838'
9842 - 9848'.

4 JSPF @ 9560 - 9569', 9607 - 9615', 9661 - 9668'.

4 JSPF @ 9380 - 9386', 9412 - 9420', 9429 - 9434'.

ITEM #27: ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

<u>DEPTH INTERVAL</u>	<u>AMOUNT AND KIND MATERIAL USED</u>
9880'	SET 5-1/2" CIBP
9724 - 9848'	2000 GALS 15% NEFE ACID
9710'	SET CIBP
9630'	SET CEMENT RETAINER W/50 SX PREM PLUS, TAILED W/50 SX PREM. NO SQUEEZE. SQUEEZE W/100 SXS OF PREM PLUS UP TO 3800 PSI.
9380 - 9434'	RBP @ 9450'. ACID'ZD W/2000 GALS 15% NEFE ACID.RE- ACID'ZD W/4000 GALS 15% NEFE ACID.