

PAGE START DATE: 1/19/9
 PAGE START TIME: 12:22: 0
 DATA FILE: 11

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	2500.00	93.50	
0.500	4320.00	104.00	
0.508	4360.00	132.25	BREAK
0.517	4393.00	122.00	
0.533	4465.00	150.50	
0.567	4613.00	114.25	
0.600	4759.00	112.00	
0.633	4911.00	113.50	
0.650	4990.00	112.25	
0.667	5074.00	114.50	
0.683	5155.00	114.00	
0.700	5239.00	115.50	
0.733	5415.00	114.25	
0.750	5507.00	119.00	
0.783	5685.00	117.25	
0.817	5859.00	120.75	
0.833	5951.00	119.50	
0.867	6140.00	122.75	
0.883	6237.00	122.00	
0.900	6335.00	123.50	
0.908	6385.00	122.75	
0.917	6434.00	125.00	
0.925	6481.00	123.50	
0.933	6528.00	126.00	
0.950	6625.00	124.50	
0.967	6724.00	126.00	
0.975	6774.00	124.25	
0.983	6823.00	126.50	
1.000	6928.00	125.25	
1.017	7034.00	127.50	
1.050	7242.00	126.75	
1.067	7341.00	130.50	
1.083	7442.00	128.50	
1.150	7862.00	131.75	
1.167	7964.00	136.25	
1.183	8066.00	135.00	
1.217	8205.00	140.50	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

JANUARY 18, 1997 @ 6:30 PM

DATE AND TIME SURVEY MADE:

JANUARY 19, 1997 @ 1:00 PM

AMOUNT AND TYPE CEMENT USED:

750 SACKS PREMIUM H, 3% ECONOLITE,
 GEL, SALT; 100 SACKS PREMIUM H RUN
 THROUGH D.V. TOOL AT 8307 FEET, BEHIND
 5½" CASING IN A 7-7/8" HOLE.

DEPTH FIGURED FROM:

GROUND LEVEL