

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33641

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

MARALO, INC.

3. Address of Operator

P. O. BOX 832, MIDLAND, TX 79702

7. Lease Name or Unit Agreement Name

DAVIS 15

8. Well No.

1

9. Pool name or Wildcat

WILDCAT (ATOKA)

4. Well Location

Unit Letter K : 1980 Feet From The SOUTH Line and 1980 Feet From The WEST Line

Section 15 Township 13S Range 38E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3808'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

COMPLETED OPERATION:

01/19/97 DRILL 7-7/8" HOLE. SET 10,005' OF 5-1/2" 17# CSG. CEMENT 1ST STAGE W/350 SXS MOD. SUPER H W/.4% CFR-3 + 5# GILSONITE + 3# SALT + .5% HALAD 344. OPEN DV TOOL AND CIRC. CEMENT 2ND STAGE W/750 SXS PREMIUM H W/5# GILSONITE + 6# SALT + 3% ECONOLITE. TAIL W/100 SXS PREMIUM H. TOC @ 4320' BY TEMPERATURE SURVEY.

CURRENT PERFORATIONS:

9726 - 9840' WOLFCAMP PLUGGED OFF W/CIBP @ 9716' + 35' CEMENT.
9181 - 9644' WOLFCAMP - OPEN

PROPOSED OPERATION: PLUG & ABANDON

1. SET CIBP @ +/- 9150' & CAP W/35' CEMENT.
2. CUT & PULL +/- 4250' 5-1/2" 17# CSG.
3. LOAD HOLE W/10#/GAL MUD LADEN FLUID
4. SET 100' CEMENT PLUG (50' IN & 50' OUT) 5-1/2" CSG STUB @ 4250'. PLUG WILL ALSO COVER 8-5/8" SHOE.
5. SET 100' CEMENT PLUG FROM 350 - 450' - ACROSS 13-3/8" SHOE.
6. CUT OFF WELLHEAD. SET 10 SACK CEMENT SURFACE PLUG. WELD ON PLATE. CLEAN UP LOCATION.

<See Attached>

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Dorothea Logan

TITLE

REGULATORY ANALYST

DATE MARCH 12, 1997

TYPE OR PRINT NAME

DOROTHEA LOGAN

TELEPHONE NO. 915 684-7441

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

MAR 19 1997

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

50

60

- 1) SET CIBP @ +/- 9150' + CAP
W/35' CEMENT.
- 2) SET 100' CEMENT PLUG 6100'-6000'
- 3) LOAD HOLE W/10⁶ GALLON MUD
LADEN FLUID.
- 4) SET 100' CEMENT PLUG (50' IN 50' OUT)
5 1/2" CSG STUB @ 4250' PLUG WILL
ALSO COVER 8 5/8" SHOE - TAG
- 5) SET 100' PLUG AT BASE OF
SALT (?)
- 6) SET 100' CEMENT PLUG F/350' to
450' ACROSS 13 3/8" SHOE.
- 7) CUT-OFF WELLHEAD - SET 10 SX
CEMENT SURFACE PLUG. WELD
ON PLATE. CLEANUP LOCATION