

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

P.O. Box 1380
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Rand Paulson Oil Company, Inc

3. Address and Telephone No.

508 W. Wall, Ste 100, Midland, Texas 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2090' FNL & 660' FEL
Sec 31 T-14-S R-35-E

5. Lease Designation and Serial No.

NM 96249

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Nicholas 31 Federal #1

9. API Well No.

30-025-33822

10. Field and Pool, or Exploratory Area

WILDCAT

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Spud, set 13 3/8, 85/8
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Norton Drilling Co. Rig No. 17.

3-20-97 Spud well @ 7 PM 3-20-97. Drill 450' of 17 1/2" hole. Ran 13 3/8" 54.5# J-55 casing to 450'. Cemented w/450 sx Class C + 2% CaCl₂. Circ cement to surface. WOC 24 hrs. Set slips, CO csg. Test casing to 600 psi.

3-22-97 NU BOP & test to 1500 psi. DO cement & shoe. Drilling 11" OH.

3-23-97 Drilling 11" hole @ 791'. Drill to 6208' & set 8 5/8" 32# S-80 & J-55 csg. Ran DV tool @ 3950. Cemented stage 1: 210 sx C + 3% D-79 @ 11.5#/gal & 2.77 ft³/sk. Tail w/200 sk C Neat. Circ DV 5 1/2 hrs. 2nd stage: 1150 sx C + 3% D-79 + 3#salt/sk @ 11.7#/gal & 2.77 ft³/sk. Tail w/200 sx C Neat. Circ 105 sx to surface. WOC 24 hrs. Cut off csg, ND BOP. Install wellhead & NU BOP. Test csg to 1000, BOP and manifold 1500 psi. DO DV tool. Drill out floats.

4-7-97 Drilling 7 7/8" hole @ 6410'.

14. I hereby certify that the foregoing is true and correct

Signed O. H. Routh Title Agent

Date 4-7-97

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side