

PROPOSED DRILLING PROGRAM
JOHN L. COX – STATE “14-A” NO. 2
SECTION 14, T-12-S, R-33-E
LEA COUNTY, NEW MEXICO

1. Spud 17 ½" hole and drill to approximately 300'.
2. Set approximately 300' of 13 3/8" 48#, J55 casing, cemented with 415 sacks Halliburton Premium Plus w/2% calcium chloride, and ¼# flocele. Cement circulated to surface.
3. Drill 11" hole to approximately 4150'.
4. Set 4,150' of 8 5/8" 32#, J55 casing cemented with 1055 sacks Halliburton Lite with ¼# flocele, 5# gilsonite, 6% gel, 6# salt and 250 sacks Premium Plus with 2% calcium chloride and ¼# flocele. Top of cement is to surface.
5. Drill 7 7/8" hole to approximately 9800'.
6. Set 9,800' of 5 ½", 17# and 20#, J55 and N80 casing cemented with 340 sacks Halliburton Lite, ¼# flocele, 3# gilsonite, 6% fluid loss, 6% gel, 6# salt and 610 sacks Premium 50/50 pozmix “A” with 2% gel, .6% fluid loss. Top of cement estimated to be approximately 4150'.
7. Well will be logged and tested for a Bagley; Penna completion.
8. BLOWOUT PREVENTERS: Shaffer LWS hydraulic double 11" x 5000 psi as illustrated in attached Diagram.

