

14" liners, 18" stroke. Compound driven
 Pump No. 2: Emeco DB300 800 H.P. powered by D379
 Caterpillar Diesel.

DRILL STRING

4,600' 4 1/2" Grade E, 20-lb.
 9,000' 4 1/2" Grade E, 18.80-lb.
 Tool Joints: 4 1/2" XH, 8 1/4" OD.
 Twenty-Seven drillcollars 6 1/2" OD, 2 1/4" ID.
 Twenty-One 8" OD x 2 1/4" ID Drill Collars
 Other sized drillpipe and drillcollars available.

BLOWOUT PREVENTERS

One Shaffer LWS hydraulic double 11" x 5,000 p.s.i. One
 Hydril 11" x 5,000 p.s.i. Choke manifold 4" x 5,000 p.s.i.
 flanged connections. Kookey Type 60, 7-station
 accumulator closing unit with remote control.

SWIVEL DROWER NOM 350 11

ROTARY TABLE. Oilwell 20 1/2

SHALE SHAKER. Totco doubi

ELECTRICAL POWER. Two 1:
 powered by diesel engines. AC
 mercury vapor lights. All vapor

FRESH WATER STORAGE. T

HOUSING. One 10' x 44' refrig
 house with sleeping and cooki



