

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.
30 025 34920

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-4569-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
STATE 14-A

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator JOHN L. COX	8. Well No. 1
3. Address of Operator Box 2217, Midland, TX 79702	9. Pool name or Wildcat Bagley Permo Penn	
4. Well Location Unit Letter G : 1330 Feet From The North Line and 2530 Feet From The East Line Section 14 Township 12-S Range 33-E NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4242 Gr.	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-27-00 - Drilling 7 7/8" hole to 9780' TD. Ran Schlumberger open hole logs

2-28-00 - Well plugged and abandoned

Set 35 sx cement plug 9780'-9680'	Approved as to plugging of the Well Bore. Liability under bond is retained until surface restoration is completed.
Set 35 sx cement plug 7404'-7304'	
Set 40 sx cement plug 5150'-5050'	
Set 75 sx cement plug 4175'-3850'	
Set 30 sx cement plug 1680'-1580'	
Set 30 sx cement plug 345'- 245'	
Set 10 sx cement plug 30'- surface	

Casing in hole: 13 3/8" @ 295' (Cement to surface)
8 5/8" @ 4125' (Cement to surface)

2-29-00 - Rig released @ 3:00 pm 2-28-00.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Martha Wittenbach TITLE Prodn. Acctng. Mgr. DATE 3/17/00

TYPE OR PRINT NAME Martha Wittenbach TELEPHONE NO 915 682-9435

(This space for State Use)

Gary W. Wink

APPROVED BY GARY W. WINK TITLE REGIONAL REPRESENTATIVE II/STAFF MANAGER DATE JAN 23 2003

5
L