State of New Mexico Form C-103 Submit 3 Copies Energy, Minerals and Natural Resources Department to Appropriate District Office Revised 1-1-89 **OIL CONSERVATION DIVISION** DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-34991 Santa Fe, New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. VA-1372 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: OIL WELL WELL X Indigo State Unit 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 9. Pool name or Wildcat 3. Address of Operator 105 South 4th St., Artesia, NM Wildcat Mississippian 4. Well Location North Unit Letter _ A · 660 Feet From The 660 East Feet From The __ Line and Line 35E Lea 12S Range Section Township **NMPM** County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4123' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: Intermediate casing & cement OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 4300'. Reached TD at 7:30 PM 6-13-2000. NOTE: Notified Sylvia w/OCD-Hobbs of intent to cement 8-5/8" casing via voice mail. Ran 97 joints of 8-5/8# 32# J-55 (4333.55') of casing set at 4300'. Regular guide shoe set at 4300' and float collar set at 4255'. Cemented with 1125 sacks Poz C (65-35), 6% bentonite, 5% salt and 1/4#/sack celloflake (yield 2.04, weight 12.5). Tailed in with 200 sacks Class C with 1% CaCl2 (yield 1.34, weight 14.8). PD 6:30 AM 6-14-2000. Bumped plug to 1900 psi, OK. Circulated 150 sacks. Nippled up and tested to 5000# for 30 minutes, OK. Drilled out at 1:30 AM 6-15-2000. WOC 19 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. SKONATURE TITLE Operations Technician D	DATE July	15, 2000
	TELEPHONE NO.	505/748-147.

(This space for State Use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY -

DATE -