

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-025-35093
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____			7. Lease Name or Unit Agreement Name Tower		
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER _____					
2. Name of Operator C. W. Trainer			8. Well No. 2		
3. Address of Operator C/O Oil Reports & Gas Services, Inc. 1008 W. Broadway, Hobbs, NM 88240			9. Pool name or Wildcat Wildcat San Andres		
4. Well Location Unit Letter M : 925 Feet From The South Line and 990 Feet From The West Line Section 23 Township 12S Range 33E NMPM Lea County					
10. Date Spudded 8/12/00	11. Date T.D. Reached 8/31/00	12. Date Compl. (Ready to Prod.) 9/16/00	13. Elevations (DF& RKB, RT, GR, etc.) 4245' GL	14. Elev. Casinghead	
15. Total Depth 4498'	16. Plug Back T.D. 4477'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools X	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 4288'-4410' San Andres					20. Was Directional Survey Made Yes
21. Type Electric and Other Logs Run GR, CBL, CCL					22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	845'	11"	275 SX	Circ. 85 sx
5 1/2	17#	4498'	7 7/8"	400 sx	Circ.

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8	4200

26. Perforation record (interval, size, and number) 4288', 90, 92, 94, 96, 98, 4300, 02, 04, 06, 08, 4313, 32, 38, 48, 56, 75, 76, 78, 80, 85, 90, 94, 4401, 07, 08, 09, 4410' (1 SPF - 28 Shots)	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 4204'-4414' 4288'-4410'	AMOUNT AND KIND MATERIAL USED 300 gals 15% acid + additives 4700 gals 15% HCL + additives + 50 RCN ball sealers in 10 stages of 5
--	---	--

28. PRODUCTION							
Date First Production 9/16/00		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping			Well Status (Prod. or Shut-in) Prod.		
Date of Test 9/21/00	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 11	Gas - MCF 0	Water - Bbl. 14	Gas - Oil Ratio ---
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate 24	Oil - Bbl. 11	Gas - MCF 0	Water - Bbl. 14	Oil Gravity - API - (Corr.) 10° gty	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)	Test Witnessed By
--	-------------------

30. List Attachments Logs, Deviation Survey, C-104

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief
--

Signature Gaye Heard	Printed Name Gaye Heard	Title Agent	Date 9/26/00
-------------------------	----------------------------	----------------	-----------------

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1670
T. Salt	1770
B. Salt	2330
T. Yates	2460
T. 7 Rivers	
T. Queen	3120
T. Grayburg	
T. San Andres	3750
T. Glorieta	
T. Paddock	
T. Blinebry	
T. Tubb	
T. Drinkard	
T. Abo	
T. Wolfcamp	
T. Penn	
T. Cisco (Bough C)	

T. Canyon
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Delaware Sand
T. Bone Springs
T. Rustler-1670
T.
T.
T.

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	1670		Red Bed
1670	2330		Salt
2330	3750		Sand & Lime