

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-35188
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

Name of Operator
Ricks Exploration, Inc.

Address of Operator
210 Park Ave., 3000 Oklahoma Tower, Oklahoma City, OK 73102

Well Location
Unit Letter P : 900' Feet From The South Line and 600' Feet From The East Line
Section 22 Township 12S Range 38E NMPM LEA County

Elevation (Show whether DF, RKB, RT, GR, etc.)

GL: 3797'

Lease Name or Unit Agreement Name

BURRUS

Well No.

2

Pool name or Wildcat

GLADIOLA-WOLFCAMP

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Drilling 100' deeper ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cmt to surface w/Redi-mix.
2. Drill 17½" hole to 400'. Run & set 400' of 13-3/8" H40 48# ST&C csg. Cmt w/440 sx of Cls C cmt + 2% CaCl + ¼# Flocele/Sx., circ cmt to surface.
3. Drill 12¼" hole to 4500'. Run & set 4500' of 9-5/8" 40# J55 St&C csg. Cmt w/900 sx of Cls C cmt + 15% gel + 2% salt + 1/4# Flocele/Sk, tail w/250 sx of Cls C cmt + 2% CaCl, circ cmt to surface.
4. Drill 8½" hole to 9800'. Run and set 9800' of 7" 26# N80 LT&C, Buttress thread. Cmt w/600 sx Class H Super Modified + additives. Estimate TOC @8200'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Lynne Suchy TITLE Drilling Asstnt DATE 3/26/01
TYPE OR PRINT NAME Lynne Suchy TELEPHONE NO. 405/516-1100

(This space for State Use)

APPROVED BY ORIGINAL SIGNATURE OF SUPERVISOR DATE MAR 29 2001
CONDITIONS OF APPROVAL, IF ANY: