			Ctoto of Now M	ovice				Farm 0 402		
Date:dit Date:dit Dit CONSERVATION DIVISION WELLAPINO Date:dit 1220 South St. Francis Drive 32-025-35208 32-025-35208 Detail Santa Fe, NM 8750 Santa Fe, NM 8750 Santa Fe, NM 8750 Detail Santa Fe, NM 8750 Santa Fe, NM 8750 Santa Fe, NM 8750 Detail Santa Fe, NM 8750 Santa Fe, NM 8750 Santa Fe, NM 8750 Detail Santa Fe, NM 8750 Be6000 Santa Fe, NM 8750 Detail Santa Fe, NM 8750 Be6000 Santa Fe, NM 8750 Detail Santa Fe, NM 8750 Be6000 Be6000 Detail Other Auterican Mutanta Research Rate Rate Rate Rate Rate Rate Rate Rate		State of New Mexico						Form C-103 Revised March 25, 1999		
Tests members bestag, will also										
Dealed 1220 South St. Francis Drive Santa Fe, NM 87505 Indicate type of Lease Santa Fe, NM 87505 Dealed Bill Acate, M 8740 Santa Fe, NM 87505 Indicate type of Lease Santa Fe, NM 87505 Dealed Bill Acate, M 8740 Base Santa Fe, NM 87505 Indicate Santa Fe, Santa Fe, NM 87505 Dealed Bill Acate, M 8740 Base Santa Fe, NM 87505 Indicate Santa Fe, Santa Fe, NM 87505 Dealed Bill Case Note To MATCH Santa Santa Fe, NM 87505 Indicate Santa Fe,							30-025-35298			
Booke Bilder, Rd., Met. NM 7100 Bu9056 Beller, M. Brace, D., Same R. M. BEGS SUNDERY NOTCES AND REPORTS ON WELLS C. Lesse Name of Unit Agreement Name: CO. Not USE THIS FORM C.R. MERCEAUS TO JAIL ON TO BEERS OF PLUG BACK TO A DEVENDENCE SEE YNFL.COM FOR PENNING YNFOR SOCI NEW MEXICO - AT - STATE C. Well X Ges Well Other B. Well No. 2. Name of Operator AMERICAN INLAND RESOURCES COMPANY, LLC. B. Well No. 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 19710 B. Fox Same or Winkat 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 19710 B. Fox Same or West 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 19710 B. Fox Same or Winkat 4. Well Loadion 110. Ebenkin (plots whole OF R, RG, RT, GR, de) B. Section 15 10. Ebenkin (plots whole OF R, RG, RT, GR, de) SUBSEQUENT REPORT OF: Exercise MIDLAND, TX 19710 10. Ebenkin (plots whole OF R, RG, RT, GR, de) COMMENCE DRILLING OPHIC DATE PLUC AND ABANDON 11. Their Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDUL WORK ALTERING CASING PULL OR ALTER CASING MULTPLE Cosing TEST AND Commente of Winkow <		a, NM 88210 Santa Fe, NM 87505								
Detect M Current D Subtrict Ministry Monitors AND REPORTS ON WELLS 7. Lease Name of Unit Agreement Name: CON OT USE THIS FORM FOR THE STAND, REPORTS ON WELLS 7. Lease Name of Unit Agreement Name: NEW MEXAGE.USE THE CALL ON FOR SUCH Convert Address of Operator Address of Operator 26 Address of Operator P.O. BOX S0938; MIDLAND, TX 79710 9. Pool name or Wildow 26 Address of Operator P.O. BOX S0938; MIDLAND, TX 79710 9. Pool name or Wildow 26 Address of Operator P.O. BOX S0938; MIDLAND, TX 79710 9. Pool name or Wildow 26 Address of Operator P.O. BOX S0938; MIDLAND, TX 79710 9. Pool name or Wildow 26 Address of Operator P.O. BOX S0938; MIDLAND, TX 79710 9. Pool name or Wildow 9. Pool name or Wildow To Check Appropriate Box to Indicate Nature of Notice, Report or Other Data 0.00000000000000000000000000000000000						6. State Oil & Gas Lease No.				
Izze Samuel 5, Hander 5, Bath E, MM 1995 SUNDARY MOTICES AND REPORTS ON WELLS CDN OT USE THIS FORM FOR PROPOSALS TO OREL OR TO DEEPEN OR FLUG BACK TO A DEFERENT RESONAL OR PROPOSALS TO CREDEN OR FLUG BACK TO A DEFERENT RESONAL STOR FOR REPORT FORM C-101) FOR SUCH PROPOSALS SI 10 - Over 11 X 21 Mane of Operator 21 Mane of Operator 22 Name of Operator 22 Name of Operator 23 Address of Operator 24 Well Location 11 Decket Appropriate 12 Township 14.5 13 Control 15 14 Well Location 11 Oncekt Appropriate Box to Indicate Nature of Notice, Report or Other Data 11 Oncekt Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDAL WORK PLUG AND ABANDON COMPLETION 01 Devide Appropriate Asset of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDAL WORK ALTERING CASING PULL OR ALTER CASING MULG AND ABANDON COMPLETION CASING TEST AND COMPLETION CASING TEST AND OTHER: Additions of completed operations. (Clearly state at pertinhere datalin, and gave pertimer data, including estinamed atal of		B-9505								
CONCIUSE THIS FOR UP ROPORES AND REPORTS ON WELLS 7. Lease Name of URIX Agreement Name: CONT USE THIS FOR UP ROPORADS TO DRILL ON TO DEEPEN OR TURB GAK TO A NEW MEXICO - AT- STATE DIFFERENT RESERVOR, USE SYMPLICATION FOR REMIT (FORM C-101) FOR SUCH NEW MEXICO - AT- STATE Otived X dees viail Other 1 Type at Welt Case viail Other 3 Address of Operator P.O. BOX 6698; MIDLAND, TX 79710 9. Pool name or Widte 3 Address of Operator P.O. BOX 6698; MIDLAND, TX 79710 9. Pool name or Widte 4 Wel Location Township 14.5 Range 33-E NMPM County Leas 10 Elevation 10. Elevation 10. Elevation (Srow Methor CR 700 PT CR 400 PT SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERNO CASING COMPLETING 011. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON COMPLETING COMPLETING COMPLETING 011. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data XANDONN XANDONN ABANDONN NEWENDIAL WORK ALTERNO CASING 011.		87505								
Difference in the intermediation intermediation in the intermediation in the intermediation intermediation in the intermediation intermediati	SU	NDRY NOTICES AND F				7. Lease Name or Unit Agreement Name:				
PROFORCILS) There is the information above is true and complete to the best of my knowledge and belief. Offwere I Completing AMERICAN INLAND RESOURCES COMPANY, LLC. 8 Well No. 26 3. Address of Operator 26 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 79710 9. Pool name of Wildoat 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 79710 9. Pool name of Wildoat 3. Address of Operator P.O. BOX 50938; MIDLAND, TX 79710 9. Pool name of Wildoat 3. Well Location Unit Letter N : 560 feet from the South 4 Weil Location Unit Letter N : 560 feet from the South South 10. Beecling (Show whether OR KRC, RT, GR, etc.) 4206 GR South										
1: Type of Weit Case Weil Other 2: Name of Operator AMERICAN INLAND RESCURCES COMPANY, LLC. 8: Well No. 3: Address of Operator P.O. Box 50939; MIDLAND, TX 79710 9: Poot name of WitiSatt 3: Address of Operator P.O. Box 50939; MIDLAND, TX 79710 9: Poot name of WitiSatt 4: Weil Location Unit Letter N : 560 feet from the South line and							NEW MEXICO -AT- STATE			
Colume X Gene Weil Other 21 Name of Operator AMERICAN INLAND RESOURCES COMPANY, LLC. 0 Well No. 23 Address of Operator P.O. BOX 50393; MIDLAND, TX 79710 0 P.Oot name or Wildsatt SAUNDERS PERMO UPPER PENN 4 Well Location Unit Letter N : 560 feet from the South ine and 4 Well Location 10. Election (Show Mather DR, RVAR, RT, GR, dec.) 200' Gene and and 10. Election (Show Mather DR, RVAR, RT, GR, dec.) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSECUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND PULL OR ALTER CASING MULTIPLE CASINO TEST AND PLUG AND ABANDONMENT VALUE RS COMPLETION CHERT Acide perfs X X 11. Descrite propeed or completed operations: Attach wellows dama or proceed completion or completion: Attach wellows data or dama or proceed completion or completion: Attach wellows data or person: X 11. Check Aprophil										
Address of Operation 26 3 Address of Operation P.O. BOX 50935; MIDLAND, TX 79710 9. Pop name or Withold 4 Weil Loadien 9. Pop name or Withold SAUNDERS PERMO UPPER PENN 4 Weil Loadien 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 4208' GR 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 4208' GR 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 4208' GR 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 4208' GR 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 4208' GR 9. Pop name or Withold 10. Elevation (Show Montro PC, RG, R7, GR, etc.) 5. SUBSEQUENT REPORT OF: 9. Pop name or Withold 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND REMEDIAL WORK Alterna Casinka Intended Casinkal Montro PLUG AND PULL OR ALTER CASING MULTIPLE Cosinki Est TAND ABANDONIMENT GRSING TEST TAND 12. Deactice proposed or completed openations Chang and propopend work)			Other							
P.O. BOX 60938; MIDLAND, TX 19710 SAUNDERS PERMO UPPER PENN 4 Weil Location Unit Letter N :: 560 feet from the South line and 1880 feet from the West line 10 Elevation (Show Marker DR, RK), RF, RF, RF, RF, RF, RF, RF, RF, RF, RF	2. Name of Operator									
4. Weil Location Unit Letter N 560 feet from the South line and 1880 feet from the Vest line Section 15 Township 14-S Range 33-E NMPM County Lea 10 Elevation (Stow Weiller OR, RKR, R7, GR, dc.) 10 Elevation (Stow Weiller OR, RKR, R7, GR, dc.) 11 Check Appropriate Box to indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEMBEDIAL WORK ALL REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEMBEDIAL WORK PLUG AND ABANDON COMPLETION CHANGE PLANS COMPLETION COMMENCE DRILLING OPNS: PLUG AND ABANDON ALL TER CASING COMPLETION COMPLETION COMPLETION COMPLETION COMPLETION COMPLETION COMPLETION COMPLETION OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER Solution completed operations (Clearly state all perform data. end pay performed date of atarting any proposed work). SEE RALE 1103. For Multiple Completions: Attach weithore diagram of proposed or origination. Og/24/01 MIRU acidizers. Pumped 1 bbi KCI down backside. Test ptr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed (@ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Set perfs Packer Packer gals Bricke, psi Rate, pm Press, psi 1st 987-9910 9823 9845 105 37d 9831- 9823 9845 105 386 700 2.0 1450 37d 9831- 9823 9845 105 386 700 2.0 1450 50 37d 9831- 9823 9845 105 387 2.0 1400 4th 9805-9815 967 961 9764-9723 9702 972	3. Address of Operator					9. Pool name or Wik	dcat			
Unit Letter N : 560 feet from the South line and 1880 feet from the West line Section 15 Township 14-S Range 33-E NMPM County Lea 10. Beaton (Slow whether DR, RK3, RT, GR, etc.) 4208' GR SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PULL OR ALTER CASING MULTIPLE COMMENCE DRILLING OPNS. PLUG AND AAANDONMENT OTHER: OCOMPLETION COMMENCE DRILLING OPNS. PLUG AND AAANDONMENT V21. OR ALTER CASING MULTIPLE CASING TEST AND COMMENCE DRILLING OPNS. PLUG AND OTHER: ACID For Mattee Completions. Attach weltore diagn of proposed and place patients dials. Including estimated attach of starting any proposed work). SEE RULE 100. For Mattee Completions. Attach weltore diagn of proposed and place of starting any proposed work). SEE RULE 100. For Mattee Completions. Attach weltore diagn of proposed and place for a follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 pis & closed (@ 230 pis. Tre			SAUNDER	RS PERMOL	JPPER PENN					
Section 15 Township 14-S Range 33-E NMPM County Lea Section 10. Elevation (Snow whather CP, RKB, RT, GP, ac) A208' GR SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. PULG AND ABANDON COMMENT Costing and proposed completion or completion or completion orepomptition or completion orepromphilition.	4. Well Location									
10. Elevation (Show whether DR, KK), R7, GR, dc.) 2008 GR 11. Check Appropriate Box to indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND PULL OR ALTER CASING MULTIPLE CASING TEST AND BANDONMENT OTHER: OTHER: Acidize perfs X 12. Departe proposed or completed operations (Clearly state all pertinent detais, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion Top Bottom Acid Perfs X 09/24/01 MILU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer Packer, psi Rate, lop Press, psi 14420 3097.99719 9823 9845 105 1387 2.0 1400 3	Unit Letter N	: 560 feet fror	n the <u>South</u> li	ine and	1880	feet from the	West	line		
10. Elevation (Show whether DR, KK), R7, GR, dc.) 2008 GR 11. Check Appropriate Box to indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND PULL OR ALTER CASING MULTIPLE CASING TEST AND BANDONMENT OTHER: OTHER: Acidize perfs X 12. Departe proposed or completed operations (Clearly state all pertinent detais, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion Top Bottom Acid Perfs X 09/24/01 MILU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer Packer, psi Rate, lop Press, psi 14420 3097.99719 9823 9845 105 1387 2.0 1400 3	Castion 15	Tourshi	n 149 P	onde		Count	h lea			
4200° GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND PLUG AND ABANDON COMMENCE DRILLING OPNS. PLUG AND ALTERING CASING OTHER: CASING TEST AND CASING TEST AND OTHER: CASING TEST AND CASING TEST AND <td col<="" td=""><td>Section 15</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td>	<td>Section 15</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	Section 15								
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND ABANDONMENT OTHER: COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT 12. Describe proposed or completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions. Attach wellbore diagram of proposed completion or recompliation. 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000K, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer gals Broke, psi Rate, bpm Press, psi 1st 9807-9910 9892 9944 630 3662 1.3 4420 2nd 9870-910 9892 9945 105 1337 2.0 1400 4th 9807-910 9892 9914 630 3662 <td< td=""><td></td><td></td><td>4208' GF</td><td>२</td><td></td><td></td><td></td><td></td></td<>			4208' GF	२						
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND PLUG AND OTHER: OTHER: COMPLETION CASING TEST AND 12. Describe proposed or completed operations (Clearly state all pottiner dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellore diagram of proposed completion. 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer gals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 9870-9874 9861 9823 920 13662 2.0 1450 3rd 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9776 588	11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data									
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB PLUG AND ABANDONMENT 12. Describe proposed or completed operations (Clearly state all pertinent datals, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach weltbore diagram of proposed completion or recomplication. OTHER: X 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treating proposed work). Set perfs Packer Packer<	NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:									
PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB ABANDONMENT 12. Describe proposed or completed operations (Clearly state all pertinent datas, and give pertinent datas, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion. OTHER: Acidize perfs X 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed (Q 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer gals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9829 2914 630 3662 1.3 4420 2nd 9870-9874 9861 9861 9863 630 3700 2.0 1650 3rd 9831- 9823 9845 105 1387 2.0 1400 4th 9808-9815 9801 9823 420 1560 2.0 1297 6th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN.	PERFORM REMEDIAL WORK	PLUG AN	DABANDON]	REMEDIAL WORK		ALTERING			
PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB 0THER: OTHER: Acidze perfs X 12. Describe proposed or completed operations (Clearly state all perfinent details, and give periment dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recomplication. X X 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Treating Set perfs Packer Packer Pals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 987-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9823 921 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9749 9669 210 1618 2	TEMPORARILY ABANDON	CHANGE	PLANS]	COMMENCE DRILLIN	ng opns. 📋				
011.0%. 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 300.00#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 01 Set perfs Packer Packer gals Broke, psi Rate, ppi Press, psi 14420 2nd 9870-9874 9861 9883 630 3700 2.0 1450 3rd 9808-9815 9801 9823										
011.0%. 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 09/24/01 MIRU acidizers. Pumped 1 bbl KCl down backside. Test pkr. to 300.00#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: 01 Set perfs Packer Packer gals Broke, psi Rate, ppi Press, psi 14420 2nd 9870-9874 9861 9883 630 3700 2.0 1450 3rd 9808-9815 9801 9823			r	7		-t				
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer gals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 9870-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9823 9845 105 1387 2.0 14400 4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 1900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 0 Load to recover = 11	OTHER: 12 Describe proposed or completer	t operations (Clearly state	all pertinent details, ar	 nd aive pe			ng any proposed			
valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer <th c<="" td=""><td colspan="9">SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.</td></th>	<td colspan="9">SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.</td>	SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.								
valve & spot valve. Valve opened at 2100 psi & closed @ 230 psi. Treated perfs as follows: Top Bottom Acid Perfs Treating Set perfs Packer Packer <th c<="" td=""><td colspan="9"></td></th>	<td colspan="9"></td>									
Top Bottom Acid Perfs Treating Set perfs Packer Packer gals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 9870-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9823 9845 105 1387 2.0 1400 4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. TITLE Operatio	09/24/01 MIRU acidizers. Pumped 1 bbl KCI down backside. Test pkr. to 3000#, OK. Release pressure and drop standing									
Set perfs Packer Packer gals Broke, psi Rate, bpm Press, psi 1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 9870-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9623 9845 105 1387 2.0 1400 4th 9808-9815 9801 9623 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal.	valve a	spot valve, valve o				aleu peris as ior				
1st 9897-9910 9892 9914 630 3662 1.3 4420 2nd 9870-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9823 9845 105 1387 2.0 1400 4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE 09/26/01	Set	norfo				Rate hnm Pr	•			
2nd 9870-9874 9861 9883 630 3700 2.0 1650 3rd 9831- 9823 9845 105 1387 2.0 1400 4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. DATE 09/26/01 Thereby certify that the information above is true and complete to the best of my knowledge and belief. DATE 09/26/01 SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE </td <td></td> <td>•</td> <td></td> <td>-</td> <td></td> <td></td> <td>••</td> <td></td>		•		-			••			
3rd 9831- 9823 9845 105 1387 2.0 1400 4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Mukael D. Puichand TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE 09/26/01										
4th 9808-9815 9801 9823 420 1560 2.0 1450 5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SKGNATURE Muchael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE 09/26/01										
5th 9776-9782 9770 9792 588 3900 2.0 1297 6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Muchael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE (915)685-0981							1450			
6th 9764-9748 9745 9767 588 1700 2.0 1118 7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SKGNATURE Mukaul D. Puidad TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer Q15)685-0981							1297			
7th 9704-9723 9702 9724 210 1700 2.0 1500 8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE 09/26/01							1118			
8th 9654-9663 9647 9669 210 1618 2.0 0 Load to recover = 1190 bbls. Swabbed back 40 bbls. Load to recover = 1150 bbls. Retrieved spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Muchuel D. Puichand TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard TITLE Operations Engineer DATE 09/26/01					0 1700	2.0	1500			
spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981		9654-9663			0 1618	2.0	0			
spot valve. Total acid = 3381 gal. SDFN. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981										
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Michael D. Prichard Type or print name Michael D. Prichard										
SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981	spot valve. Total acid = 3381 gal. SDFN.									
SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981										
SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981										
SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981										
SIGNATURE Michael D. Prichard TITLE Operations Engineer DATE 09/26/01 Type or print name Michael D. Prichard (915)685-0981	I hereby certify that the informatic	n above is true and com	plete to the best of m	y knowle	edge and belief.					
Type or print name Michael D. Prichard (915)685-0981										
Type of plant halfe	SIGNATURE /// WALLY U. [WARAN TITLE Operations Engineer DATE 09/26/01									
Type of plant halfe	Tume or print name Michael	D. Prichard				Telent	none No	(915)685-0981		
					· · · · · · · · · · · · · · · · · · ·					

TITLE

DATE

1 1 1

APPROVED BY: Conditions of approval, if any: