

State of New Mexico  
Energy, Minerals and Natural Resources Department

DISTRICT I  
P.O. Box 1980, Hobbs NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO  30-025-35327
5. Indicate Type of Lease State <input checked="" type="checkbox"/> FEE
7. Lease Name or Unit Agreement Name  North Papalotes State Unit
8. Well No.  1
9. Pool Name or Wildcat  Wildcat Mississippian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator  Yates Petroleum Corporation
3. Address of Operator  105 South 4th., Artesia, NM 88210	4. Well Location Unit Letter <u>A</u> : <u>990</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>36</u> Township <u>14S</u> Range <u>34E</u> NMPM <u>Lea</u> COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.)  4064' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/11/01-TD 5990'. TD 11" hole @ 8:45 pm 4-10-01. NOTE: Notified Sylvia Dickey with NMOCD Hobbs of intent to run 8 5/8" casing and cement same. Ran 141 jsts 8-5/8" 32# N-80 + J-55 (5994') casing, set @ 5990'. Regular guide shoe set @ 5990'. Float collar set @ 5946'. Cemented with 3550 sacks C + Poz 35.65 + 6% gel + 4# LCM-1 + 1/4# celloflake (yld 2.02, wt 12.5). Tailed in w/200 sacks "C" Neat (yld 1.33, wt 14.8) PD @ 5:00 pm 4-11-01. Bumped plug to 2150 psi, held OK. Circulated 589 sacks. WOC. Nipped up and tested to 5000 psi for 30 min. Nipped up BOP, tested BOP to 5000# for 30 min, OK. Drilled float, shoe & cement. Tested casing to 1000#, OK drilled out @ 10:45 pm 4-12-01. WOC 30 hrs 45 min. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is a true and complete to the best of my knowledge and belief.

SIGNATURE Donna Clack TITLE Operations Technician DATE 10/25/01  
TYPE OR PRINT NAME Donna Clack TELEPHONE NO 505-748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_