

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-025-35566
5. Indicate Type of Lease
STATE ☐ FEE ☐
6. State Oil & Gas Lease No.
28026

7. Lease Name or Unit Agreement Name:
Sprouting PMD

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
David H. Arrington Oil & Gas, Inc

8. Well No.
1

3. Address of Operator
P.O. Box 2071, Midland, Texas 79702

9. Pool name or Wildcat
Wildcat Mississippian

4. Well Location

Unit Letter L: 1980' feet from the South line and 660' feet from the West line

Section 28 Township 12S Range 35E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
4093' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER Temporarily Abandon Well ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER Set Surface & Intermediate Casing ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Well will be temporarily abandon as follows:

1. Set plug at (Mississippian) 13,078'-12,978' with 65 sxs Class "H" cement & tag.
2. Set plug at 11,480'-11,380' with 60 sxs Class "H" cement.
3. Set plug at 9500'-9400' with 60 sxs Class "H" cement.
4. Set plug at 7270'-7170' with 60 sxs Class "H" cement.
5. Set plug at 5825'-5725' with 60 sxs Class "C" cement.
6. Set cement plug across intermediate shoe at 4490'-4390 with 50 sxs Class "C" cement & tag.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chuck Sledge TITLE Engineer DATE 9/20/01

Type or print name Chuck Sledge Telephone No. (915) 682-6685

(This space for State use)

APPROVED BY _____ TITLE _____ DATE 9/20/01

Conditions of approval, if any: