

DISTRICT I
P.O. Box 1980, Hobbs NM 88240
DISTRICT II
P.O. Drawer DD, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department
OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088


(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-35761
1. Type of Well: OIL <input type="checkbox"/> GAS <input type="checkbox"/> WELL <input type="checkbox"/> WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. Indicate Type of Lease State <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		7. Lease Name or Unit Agreement Name VO-5093 Mocha State Unit
3. Address of Operator 105 South 4th., Artesia, NM 88210		8. Well No. 1
4. Well Location Unit Letter C : 1100 Feet From The North Line and 1980 Feet From The West Line Section 2 Township T13S Range R34E NMPM Lea COUNTY		9. Pool Name or Wildcat Wildcat Mississippian
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4102' GR		

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER Production Casing <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-17-02 - TD 8-3/4" hole @ 4:00 am MST. Ran 307 jts 17# & 20# P110, L80, and J-55 5-1/2" casing, set @ 13000'. Float shoe set @ 13000'. Float collar set @ 12957'. Cemented with 1900 sx Super H + 1# salt + 5/10% Halad 344 + 4/10% CFR-3 + 5# Gilsonite + 1/10% HR-7 (yield 1.66, wt 13). Sandblasted zones 13000-11552', 10920-9974', 9300-9085'; cmt assisted w/150 SCF nitrified mud. Maintained full returns throughout cmt job. Brought cmt top to approximately 7000'.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Tech DATE 5/20/02
TYPE OR PRINT NAME Stormi Davis TELEPHONE NO 505-748-1471

(This space for State Use)
APPROVED BY PAUL F. KAUTZ TITLE PETROLEUM ENGINEER DATE MAY 29 2002
CONDITIONS OF APPROVAL, IF ANY:

150