

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## REQUEST FOR (OIL) - (GAS) ALLOWABLE

New Well  
Recompletion

This form shall be submitted by the operator before an initial allowable will be assigned to any completed Oil or Gas well. Form C-104 is to be submitted in QUADRUPPLICATE to the same District Office to which Form C-101 was sent. The allowable will be assigned effective 7:00 A.M. on date of completion or recompletion, provided this form is filed during calendar month of completion or recompletion. The completion date shall be that date in the case of an oil well when oil is delivered into the stock tanks. Gas must be reported on 15.025 psia at 60° Fahrenheit.

Tatum, New Mexico February 15, 1954  
(Place) (Date)

WE ARE HEREBY REQUESTING AN ALLOWABLE FOR A WELL KNOWN AS:

Amerada Petroleum Corporation Federal "C" Well No. 1, in C/NE 1/4 SE 1/4,  
(Company or Operator) (Lease)  
I, Sec. 10, T. 7-S, R. 32-E, NMPM, Wildcat Pool  
(Unit)  
Roosevelt County. Date Spudded 11/5/53, Date Completed 1/28/54

Please indicate location:

32-E			
Section 10			
			#1

1980' FSL &amp; 660' FEL

Casing and Cementing Record

Size	Feet	Sax
13-3/8	300'	250
8-5/8	3375'	1500
5-1/2	9360'	500

Elevation 4474' D.F. Total Depth 9637' P.B. 9275'  
(by Schlumberger Not defined -  
Top oil/gas pay 9210' survey) Prod. Form Pre-Mississippian  
Casing Perforations: (9229' to 9245') and (9255' to 9270') or  
Depth to Casing shoe of Prod. String 9360'  
Natural Prod. Test --- BOPD  
based on --- bbls. Oil in --- Hrs. --- Mins.  
Test after acid or shot 186.72 BOPD  
Based on 77.80 bbls. Oil in 10 Hrs. 00 Mins.  
Gas Well Potential ---  
Size choke in inches (Swabbing)  
Date first oil run to tanks or gas to Transmission system: February 13, 1954  
Transporter taking Oil or Gas: Tide Water Associated Oil Company

Remarks: 1st stage - acidized 5 1/2" casing perf. (9255' - 9270') w/ 500 gal. Dowell 15% LST acid; acidized 5 1/2" esg. perf. (9229' - 9245') w/ 500 gal. Dowell 15% LST acid. 2nd stage - Acidize 5 1/2" casing perf. (9255' - 9270') and (9229' - 9245') simultaneously w/ 2000 gal. Dowell 15% LST acid. Swabbed 77.80 bbls oil and 25.79 bbls acid water in 10 hrs. Gravity - 45.1 Corrected

I hereby certify that the information given above is true and complete to the best of my knowledge.  
Approved: FEB 18 1954, 19Amerada Petroleum Corporation  
(Company or Operator)By: J. J. Thompson  
(Signature)Title Assistant District Superintendent  
Send Communications regarding well to:

Name Amerada Petroleum Corporation

Address Roswell Star Route Tatum, New Mexico

OIL CONSERVATION COMMISSION

By: S. G. Stanley

Title

