

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

1954 MAY 19 AM 8:49

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Tatum, New Mexico
(Place)

May 17, 1954
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation (Company or Operator) **Floyd Vincent** Well No. **1** in **MM** (Unit)
SW 1/4 **SW** 1/4 of Sec. **11**, T. **7-S**, R. **32-E**, NMPM., **Undesignated** Pool
Roosevelt County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

10,295' Total Depth - Line. Ran Schlumberger surveys. Drill stem test of section 10,215' to 10,295' - no show of oil or gas - recovered 720' of salt water. We propose to plug and abandon well @ present depth. Cement plugs to be placed as follows:

- A 35 sx cement plug from 10,086' to 10,200'
 - A 35 sx cement plug from 9038' to 9150'
 - A 35 sx cement plug from 3314' to 3427'
- and a 10 sx cement plug in top of 13-3/8" OD casing.

Hole to be filled with heavy drilling mud between all cement plugs. On setting 8-5/8" OD casing @ 3372' cement circulated outside of casing to point 28' from surface. No salvage of 8-5/8" OD casing is planned.

A piece of 4" line pipe will be cemented in top of 13-3/8" OD casing and extend five feet above ground level to serve as abandoned well marker.

Approved....., 19.....
Except as follows:

Amerada Petroleum Corporation
 By **J. W. Wiseman**
 Position **Foreman**
 Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION
 By **L. J. Stanley**
 Title.....

Name **Amerada Petroleum Corporation**
 Address **Roswell Star Route Tatum, New Mexico**

