

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED

SEP 10 1951

OIL CONSERVATION COMMISSION

RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within the time specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 8, 1951 Amarillo, Texas

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Baker & Taylor Drilling Co. Tom Best Well No. No. 1 in the

SW/4SW/4 of Sec. 25, T. 2S, R. 30E, N. M. P. M.,

Wildcat Field Roosevelt County.

The dates of this work were as follows: Spudded in 8/31/51, set surface casing 9/7, tested casing 9/8

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19____

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well spudded August 31, 1951. Drilled 12-1/4" hole to 630 ft. Reduced size of hole to 11" to 1150 ft. Ran 1150' 8-5/8" 32# seamless Spang casing. Cemented with 200 sacks cement. Job completed 7:00 A. M. Cement set 24 hours, tested with 300 pounds for 30 minutes, no pressure lost. Drilled plug and cement, tested with 300# for 30 minutes after plug drilled, no pressure lost. Elevation rotary drive bushings 4505 ft. Ground elevation 4490 ft.

Witnessed by Max E. Banks Name BAKER & TAYLOR DRILLING CO. Title Drilling Sup

Subscribed and sworn before me this 8th

day of September, 19 51

Marilyn Rascher
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name W. W. Carter

Position Asst. Secretary-Treas.

Representing BAKER & TAYLOR DRILLING CO.
Company or Operator

My commission expires June 1952

Address 712 1st Natl. Bldg., Amarillo, Texa

Remarks:

APPROVED

Date SEP 10 1951

Ray Yankrough
Name
Oil & Gas Inspector