

**WELL RECORD**

AREA 640 ACRES  
LOCATE WELL CORRECTLY

### OIL SANDS OR ZONES

## IMPORTANT WATER SANDS

No. 1, from 155 to 165 feet.

No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.

No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.

No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

### CASING RECORD

[illegible]

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
6 3/4	None		none	none	11lbs.m	
Drilled to 3370 feet, and plugged with 30 sacks of cement. Left all 7 inch in well. Drilled into sulphur water at 3363 feet.						

## PLUGS AND ADAPTERS

Heaving plug—Material.....None.....Length.....Depth Set.....  
Adapters — Material.....None.....Size.....

### RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment.....None

### RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 3370 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from none feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## PRODUCTION

Put to producing.....none....., 19.....

The production of the first 24 hours was.....barrels of fluid of which.....% was oil; .....% emulsion; .....% water; and.....% sediment. Gravity, Be.....

If gas well, cu. ft. per 24 hours.....Gallons gasoline per 1,000 cu. ft. of gas.....

Rock pressure, lbs. per sq. in.....

## EMPLOYEES

....., Driller ..... , Driller  
R.B.Myles Drilling Co Driller Joe Kountz Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 21  
day of April, 19 48

Portales, New Mexico April 21-48

Place Date

Name *N. J. [Signature]*

Position Owner

Representing Himself

Company or Operator

Address Portales, New Mexico

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	16	16	Caliche
16	110	94	Sand & Shale
110	160	50	Lime shells, shale
160	170	10	Fresh water
170	375	205	Sandy shale
375	380	5	Floating oil sand
380	600	220	Red Shale, sandy shale
600	625	25	Oil Sand, no gas
625	645	20	Dark Brown Lime
645	960	315	Red Beds
960	1060	100	Red Beds & Limeshells
1060	1129	69	Red beds, Limestreaks, solid lime 1113-1129 feet.
1129	1134	5	Oil Sand
1134	1136	2	Hard Lime
1136	1146	10	Oil Sand
1146	1156	10	Hard Buff Lime
1156	1510	354	Red Beds, Anhydrite, salt 1487 feet
1510	2143	633	Red Beds, salt, anhydrite, shale, top
2143	2240	97	Red Sand
2240	2560	320	No Lime. Instead Red Rock. In place of Gray & Brown Lime.
2560	3320	760	Salt anhydrite, & red shale
3320	3340	20	Potash
3340	3370	30	<del>XXXXXXXXXX</del> San Andreas Lime.
			Sulphur water 3370 feet. Plugged with 40 sacks. Left all pipe in the well. Placed regular surface marker at well site.
			Signed W.J. Peterman, Operator,
			April 21, 1948