



FORM C-105

TRIPPLICATE

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

W. J. Peterman Company of Operator Portales, New Mexico
Frank & Ola Taylor Well No. 1 in Center SW 1/4 Sec. 22, T. 28
R. 30E N. M. P. M. Claudell Field, Roosevelt County.
Well is 660 feet south of the North line and 1143 feet west of the East line of & 1980'E of W. line 22
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Frank & Ola Taylor Address Fort Worth, Tex.
If Government land the permittee is Address
The Lessee is W. J. Peterman Address Portales, N. M.
Drilling commenced Jan 27 19 44 Drilling was completed June 6 19 44
Name of drilling contractor R. B. Myles Address Lubbock, Tex
Elevation above sea level at top of casing 4589 feet.
The information given is to be kept confidential until none 19

OIL SANDS OR ZONES

No. 1, from 597 to 623 No. 4, from to
No. 2, from 1126 to 1143 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 155 to 165 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
7"	28	8	Seamless 1500 Texas	Cemented	100	scks.,	Halliburton		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
8 3/4"	7"	1,500	100	Halliburton	11pd., mud	circulation cap.,

PLUGS AND ADAPTERS

Heaving plug—Material none Length none Depth Set none
Adapters — Material none Size none

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment.
None

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 2330 feet, and from feet to feet
Cable tools were used from none feet to feet, and from feet to feet

PRODUCTION

Put to producing none 19
The production of the first 24 hours was none barrels of fluid of which none % was oil; none % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

(Myles Drilling Co., Driller Joe Kountz Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 21st Portales, New Mexico, April 21st.,
day of April 21st., 19 48. Name [Signature]
Notary Public Position
Representing Himself
Company or Operator
My Commission expires March 1, 1954 Address Portales, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	18	18	Chaliche
18	110	92	Sand, Shale
110	155	45	Lime Shells & Shale
155	165	10	Fresh water
165	370	205	Sandy shales, Red
370	375	5	Oil show, floating sand
375	597	220	Red Shale & sandy Shale
597	623	26	Oil Sand, no gas
623	643	20	Dark Brown Lime
643	950	307	Red Beds
950	1050	100	Red Beds & Light Lime Streaks
1050	1110	60	Red Beds & Lime Shells
1110	1126	16	Hard Buff colored Lime solid
1126	1131	5	Oil Sand
1131	1133	2	Hard Lime Shell
1133	1143	10	Oil Sand
1143	1153	10	Hard Buff Lime
1153	1500	347	Red Beds, Anhydrite, & salt 1480'
1500	2138	638	Red Beds, Salt, Anhydrite, top Red Sand 2138 feet.
2138	2245	107	Red Sand, Dry, and hard
2245	2330	85	Salt, Anhydrite.

7 Inch casing cemented at 1,500 feet broke lose, and came down the hole. Cemented with 30 sacks, and plugged well, with Marker at surface, leaving all of 7 inch in the well.

Signed W.J. Peterman, Operator

April 21, 1948