

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
MISCELLANEOUS REPORTS ON WELLS

RECEIVED

AUG 22 1951

OIL CONSERVATION COMMISSION
WORKS OFFICE

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on running additional casing to top of anhydrite	<input checked="" type="checkbox"/>

August 17, 1951

Elida, N.M.

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the Lynn-Greer

Well M.G. Vinther Well No. One in the
 Company or Operator SE/4 of NE/4 Lease
 of Sec. 14, T. 3 South, R. 30 East, N. M. P. M.,
 Wildcat Roosevelt Pool County.

The dates of this work were as follows: August 17, 1951 & probably finish August 21-22, 1951.

Notice of intention to do the work was (was not) submitted on Form C-102 on verbal, 19____,
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On August 13, 1951, ran 597 feet of 10-3/4 inch casing to stop caving. Ran into more water at 635 feet and at 675 feet (salt water); drilled to 820 and well began to cave. Under-reamed to 820 and started running additional 10-3/4 inch casing on August 17 & to bottom on August 19, 1951. Am now under-digging additional pipe to carry same to the top of the anhydrite at approximate depth of 1200 feet. Should hit it between 1190 and 1200 feet. Have 1215 feet of 10-3/4 inch casing on rack ready to run and same will be set on top of the anhydrite... as per recent conversation with Mr. Roy Yarbrough, Chief Inspector, Oil Conservation Commission, Hobbs, N.M.

Witnessed by _____ Name _____ Company _____ Title _____

APPROVED:
OIL CONSERVATION COMMISSION

Roy Yarbrough
 Oil & Gas Inspector
 Name _____
 Title _____

AUG 22 1951

Date

I hereby swear or affirm that the information given above is true and correct.

Name R. P. Lynn
 Position Trustee.
 Representing Lynn-Greer Well
 Company or Operator
 Address 2201 Waco St.,
San Angelo, Texas.