

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Portales, New Mexico

Place

November 14, 1949

Date


OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

W.J. Peterman, Operator McCabe Foust Hilburn Well No. 1 in center SESW  
Company or Operator Lease

of Sec. 31, T. 2S, R. 31E, N. M., P. M., Claudell Field, Roosevelt County.



AREA 640 ACRES

LOCATE WELL CORRECTLY

The well is 660 feet (N.) (S.) of the south line and 660 feet (E.) (W.) of the east line of SE of the SW.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is Travis B. McCabe, J.C. Hilburn & E.J. Foust

Address Elida, New Mexico

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

We propose to drill well with drilling equipment as follows: Rotary to 3,500'

carrying 8 inch hole to 3,500' or deeper

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Shank Cement
11 3/4	9"	34pd.,	New	1,100'	cemented	50scks.,

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 2,950 feet.

Additional information: Should drill stem test indicate production in San Andreas at around 2,950', 5 1/2 inch will be cemented. Otherwise drilling will be carried on to the Glorieta sand at around 3,276', and tested.

JAN 4 1950

Approved \_\_\_\_\_, 19\_\_\_\_

except as follows:

Sincerely yours,

W.J. Peterman, Operator

Company or Operator

By \_\_\_\_\_

Position Operator

Send communications regarding well to

Name W.J. Peterman

Address Portales, New Mexico

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

Title \_\_\_\_\_

