


# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Report on water shut off

April 20, 1948  
Date

Portales, New Mexico  
Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the 1680' E of W line & 960' N of S. Line of W. J. Peterman Company or Operator Frank & Ola Taylor Lease Well No. 2 in the Taylor No. 2 Field of Sec. 22, T. 29, R. 30E, N. M. P. M., Roosevelt County.

The dates of this work were as follows: Feb. 3, 1946 cemented 4 1/2 inch pipe

Notice of intention to do the work was (was not) submitted on Form C-102 on April 20-1948 1948 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**  
4 1/2 inch hung in hole at 1122 feet instead of reaching casing point at 1129 feet. Cemented with 10 sacks at 1122 feet, on Feb. 3rd., let set until Feb. 5th. Drilled cement set in pipe for 10 feet. Bailed well down, and tested for water shut off. O.K.

Drilled well into oil sand at from 1152 to 1170 feet. Bailed heavy oil & gas out rotary mud at rate 5bbls. per hour while well free of caves from 1129 feet on down to bottom. Dumped 10 sacks with bailer in bottom of hole. left all 4 1/2 inch pipe in hole, and placed regulation marker

Witnessed by W. J. Peterman Name W. J. Peterman Company Owner Title Owner

Subscribed and sworn before me this 21st day of April 48

I hereby swear or affirm that the information given above is true and correct.

Name W. J. Peterman

Position Owner

Representing Himself Company or Operator

Notary Public

My commission expires March 1, 1951

Address Portales, New Mexico


Remarks:

*Ray Yudenberg*  
 OIL & GAS INSPECTOR

Name

Title

Detailed description of Figure 1: The graph plots the percentage of total catch against the number of hauls for 15 different fish species. The species are listed on the x-axis: *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, *Chelodactylus*, and *Chelodactylus*. The y-axis represents the percentage of total catch, with a scale from 0 to 100. A legend at the top right provides a key for the percentage values: 1.0 = 100%, 0.5 = 50%, 0.2 = 20%, 0.1 = 10%, 0.05 = 5%, 0.02 = 2%, 0.01 = 1%, 0.005 = 0.5%, 0.002 = 0.2%, 0.001 = 0.1%.



*[Handwritten signature]*

Handwritten signature: *Handwritten signature*