

COUNTY <u>Roosevelt</u> FIELD <u>Wildcat</u>										STATE <u>N.M.</u> NO.									
WC OPR. <u>Wilson, Max M.</u>										MAP									
NO. <u>1</u> LSE <u>Cox</u>																			
SEC. <u>33</u> T. <u>5S</u> BLK. <u>36E</u> SUR.										CO-ORD.									
LOC. <u>660' fr S Line & 2030' fr W Line of Sec.</u>																			
MI. FROM <u>P&A</u>										CLASS. EL. <u>4043.8</u>									
SPUD. <u>12-30-63</u> COMP. <u>1-26-64</u>										FORMATION DATUM FORMATION DATUM									
IRT										LOG:									
										SA 3260									
CSG. & SX.										Glor 4605									
8 5/8" 304' 225																			
5 1/2" 4710' 225																			
TBG. DEPTH SIZE																			
LOGS EL GR RA IND HC A																			
										TD 4714' PB									
PROD INT. (DAILY RATE)										BS&W GH GOR GTY C. P. T. P. HRS. TEST									
PLUGGED & ABANDONED																			
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.																			
CONT. DATE										PROP DEPTH <u>4750'</u> TYPE									

F.R. 11-7-63

PD 4750' - San Andres

1-6-64

Drlg. 3942'.

1-13-64

TD 4700', running logs.

Cored 3945-91', rec 46' anhy. & dolo., W/PP & Sli. vuggy poro. 3960-68' & 3973-79'.

Cored 4170-4220', rec 50' dolo., w/NS.

1-20-64

TD 4714' (Corr.), prep to perf.

1-27-64

TD 4714', PLUGGED & ABANDONED.

Perf 4702-06' W/2 SPF

Ac. 500 gals

Swbd acid wtr, with no shows.

Perf 4570-73' W/2 SPF

swbd salt wtr, with show gas.

Perf 4577-81' & 4587-93' W/2 SPF,

Ac. 1000 gals

swbd salt wtr.

Roosevelt Wildcat NM.
Wilson, Max M. #1 Cox - Sec. 33-5S-36E

Page 2

1-27-64

-cont-

Set BP @ 4550',

Perf 4542-48' W/2 SPF

Ac. 1000 gals,

swbd salt wtr,

Set BP @ 4350',

Perf 4334-42' W/2 SPF

Ac. 1000 gals

swbd dry.

Set BP @ 4225'.

Perf 4176', 4180', 4189', 4193', 4199',

4209', 4218' & 4222' W/1 SPI

Ac. 1500 gals,

swbd dry.