

COUNTY **ROOSEVELT** FIELD **Wildcat** STATE **NM** MAP

OPR **PENROC OIL CORPORATION** CO-ORD

1 State **MX 10599**

Sec. **32, T-6-S, R-35-E**

660' FNL, 1980' FWL of Sec.

Spd **7-11-66**

Cmp **8-5-66**

CSG & SX - TUBING	CLASS			
	FORMATION	DATUM	FORMATION	EL
8 5/8" 411' 150				
4 1/2" 4365' 325				

LOGS EL GR RA IND HC A

PLUGGED & ABANDONED

TD 4365'

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Consulting Service, Inc.

CONT. WEK Drlg. Co. PROP DEPTH **4500'** TYPE

DATE

F.R. 6-30-66; Opr's Elev. 4271' GL

PD 4500' - SA

Contractor - WEK Drlg. Co.

7-11-66 Prep to Spud

7-18-66 Drlg. 3497' anhy & dolo.

7-25-66 Coring @ 4286'

Cored 4188-4239', rec 49' dolo & anhy.,
 bldg oil 4200-07'.

8-1-66 TD 4365', prep to Acid.

Cored 4239-93', rec 54' anhy & dolo., w/scatt
 bldg oil, trace of salt wtr in bottom 3'.

Cored 4293-4343', rec 50' dolo & anhy., w/fair
 scatt poro., bldg oil & salt wtr.

Perf @ 4286', 4289', 4296', 4303', 4306',
 4318', 4322', 4331' W/1 SPI

Swbd dry

ROOSEVELT Wildcat
PENROC OIL CORP., #1 State NM

Sec. 32-6S-35E
Page #2

8-8-66 TD 4365', PBD 4240', PLUGGED & ABANDONED.
Acid (4286-4331') 2000 gals.
Swbd 4 B Form Wtr PH, w/tr. oil. (4286-4331')
Set BP @ 4240'

Perf @ 4071', 4073', 4075', 4187', 4189',
4191', 4193' W/1 SPI

Swbd dry

Acid (4071-4193') 2000 gals.

Swbd dry, w/tr. oil & gas (4071-4193')
(Holding for tops)

8-15-66 TD 4365', PBD 4240', Completion Reported.
LOG TOPS: Yates 2290', Queen 2963',
San Andres 3434'.

Feb 10 1971

074-66

~~074-66~~

074-66

101 10-10-71

32 6-38