

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.  
NEW MEXICO OIL CONSERVATION COMMISSION  
APR 11 11 41 AM '67

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name <b>Tenneco-Foster "28"</b>
9. Well No. <b>1</b>
10. Field and Pool, or Wildcat <b>Wildcat</b>
12. County <b>Roosevelt</b>

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Dry Hole</b>
2. Name of Operator <b>David Fasken</b>
3. Address of Operator <b>608 First National Bank Bldg., Midland, Texas</b>
4. Location of Well UNIT LETTER <b>C</b> , <b>1980</b> FEET FROM THE <b>West</b> LINE AND <b>660</b> FEET FROM <b>North</b> LINE, SECTION <b>28</b> TOWNSHIP <b>6-S</b> RANGE <b>37-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>4020 GR</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled 7-7/8" hole to 4775'.
2. Hole filled with mud, 10.2#/gal., 43 Sec. viscosity, 9.6cc water loss.
3. Plugging approved in telephone conversation - Henry to Engbrecht April 4, 1967.
4. Spotted cement plugs as follows:
  - 25 sacks at 4750' San Andres-Glorietta contact
  - 25 sacks at 3450' Top San Andres
  - 25 sacks at 2350' Top Yates
  - 25 sacks at 2120' Top Rustler
  - 25 sacks at 360' Base Surface Casing
  - 10 sacks at Surface
5. Plugged and abandoned 11:00 P.M. MST 4-4-67.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James B. Henry TITLE Agent DATE 4-7-67  
APPROVED BY John W. Runyan TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: