

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 MAY 23 1 50 PM '67

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		5. State Oil & Gas Lease No. None
2. Name of Operator Redfern Development Corporation		7. Unit Agreement Name None
3. Address of Operator P. O. Box 1747, Midland, Texas 79701		8. Farm or Lease Name Wiseman
4. Location of Well UNIT LETTER I 1989 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 6S RANGE 33E NMPM.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 4354 Ground Level		10. Field and Pool, or Wildcat Wildcat
		12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Permission to plug and abandon and approval of plugging program were received verbally on April 24, 1967, from the District I Office. All plugging was performed on April 26, 1967. Set regular neat cement plugs as follows: 3910' to 3810' (100') with 30 sacks, 3125' to 3075' (50') with 25 sacks, 2050' to 2000' (50') with 25 sacks, 1850' to 1800' (50') with 25 sacks, 410' to 360' (50') with 25 sacks and surface to 20' below ground level with 10 sacks.

The 7-7/8" open hole drilled to 4150' total depth was reamed to 9-7/8" from 387' to 3210' prior to start of plugging operations. At time of plugging, hole was loaded with mud having a weight of 10.4 lbs. per gal. Plugs were spotted through 4-1/2" O.D. drill pipe. A steel marker was set at the surface.

All of the 10-3/4" O.D. surface casing set at 384' was left in the hole; no other casing strings were run.

Pits filled and location levelled and cleaned.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John A. Weideman TITLE Agent DATE May 22, 1967

APPROVED BY John W. Remy TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: