NO. OF COPIES NUCEIVED]		_
DISTRIBUTION		•	Form C-103 Supersedes Old
SANTA FE		ERVATION COMMISSION	C-102 and C-103
FILE		ERVATION COMMISSION	Effective 1-1-65
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE	-	1 1 7	State Fee X
OPERATOR]		5. State Oil & Gas Lease No.
SUNDR (DO NOT USE THIS FORM FOR PR USE "APPLICAT	RY NOTICES AND REPORTS ON OPOSALS TO DRILL OR TO DEEPEN OR PLUG B TION FOR PERMIT (FORM C-101) FOR SUC	WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.)	
OIL AS WELL AS	OTHER-		7. Unit Agreement Name
2. Name of Operator			8. Farm or Lease Name
The Eastland Drilling Company			W. G. Victor
3. Address of Operator		· · · · · · · · · · · · · · · · · · ·	9. Well No.
730 Petroleum Life Building, Midland, Texas 79701			1
4, Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER M	660 FEET FROM THE South	LINE AND 660 FEET FR	Wildcat
THE <u>West</u> Line, Section	ON 34 TOWNSHIP 45	RANGE 35E NMP	*• (AIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
	15. Elevation (Show whether	DF, RT, GR, esc.)	12. County
$\frac{16}{16}$		5 GL	Roosevelt AllIIII
Check	Appropriate Box To Indicate N	ature of Notice, Report or C	Other Data
			NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	
TEMPORARILY ABANDON			ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
OTHER		OTHER	
		·	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total depth of 4619' was reached November 18, 1967. The 8 5/8" surface casing was set @ 344' with cement circulated. A 7 7/8" hole was drilled to total depth. Plugging operations were begun at 2:00 P.M. November 20, 1967 and were completed at 11:45 P.M. November 20. The hole was filled with 10.1# per gallon drilling mud and plugs were displaced with 10.1# per gal mud through 3 1/2" drill pipe. Plugs were set as follows:

25 sacks cement from 4619 to 4530' on bottom 25 sacks cement from 3250 to 3163' at top of San Andres 25 sacks cement from 1480 to 1393' at top of salt 25 sacks cement from 390 to 303 ' in bottom of 8 5/8" casing 10 sacks cement from 30 to surface in top of 8 5/8" casing

No casing was pulled. A 4" X 4' steel marker was installed showing required information. Notification was be given when location is clean and ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

signed from Theal	TITLE Superintendent	DATE NOV. 22, 1967
APPROVED John W. Runyan CONDITIONS OF APPROVAL, IF ANY:	тітье (1.0.1021)	DATE