

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator The Eastland Drilling Company		8. Farm or Lease Name J. A. Cooper
3. Address of Operator 730 Petroleum Life Building, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER K , 1980 FEET FROM THE West LINE AND 1980 FEET FROM THE South LINE, SECTION 12 TOWNSHIP 5S RANGE 30E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4565 RKB		12. County Roosevelt

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total depth of 4200 feet was reached December 7, 1967. A 7 7/8" hole was drilled below the 8 5/8" surface casing set at 370 feet. Plugging operations were begun at 9:00 P.M., December 9, 1967 and were completed at 8:00 A.M., December 10, 1967. The hole was filled with 10.5# per gallon drilling mud and plugs were displaced with 10.5# per gallon mud through 3 1/2" drill pipe. Plugs were set as follows:

- 25 sacks cement from 4200' to 4125' on bottom.
- 25 sacks cement from 3234' to 3159' at top of San Andres
- 25 sacks cement from 1465' to 1390' at top of salt.
- 25 sacks cement from 400' to 325' in bottom of 8 5/8" casing
- 10 sacks cement from 30' to surface in top of 8 5/8" casing

No casing was pulled and cement was circulated around surface pipe. A 4" X 4' steel marker was installed showing required information. Notification will be given when location is clean and ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>George L. Dehal</u>	TITLE <u>Superintendent</u>	DATE <u>Dec. 11, 1967</u>
APPROVED BY <u>John W. Runyan</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		