

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Taylor Pruitt	8. Farm or Lease Name Atlantic Tucker
3. Address of Operator c/o Oil Reports & Gas Services, Box 763, Hobbs, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 7 S RANGE 32 E N.M.P.M.	10. Field and Pool, or Wildcat Undes. Chaveroo-SA
15. Elevation (Show whether DF, RT, GR, etc.) 4437.9 GR	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole 6:00 PM 12/10/67. Cemented 8 5/8" 20# casing at 344 feet with 225 sacks Longhorn Portland cement 2% calcium chloride. Cement circulated. Plug down 12:01 AM 12/11/67. WOC 18 hours and pressure tested casing with 1,000# for 30 minutes, test O.K.

Cemented 5 1/2" 15.5# J-55 casing at 4411 with 300 sacks Halliburton light cement and 300 sacks Pozmix Incor Class "C", 0.75% CFR-2, 2% gel with 11# salt per sack. Bumped plug with 1700# 3:30 PM 12/20/67. WOC 24 hours and pressure tested casing with 1,000# for 30 minutes, test O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Donna Hollis</i></u>	TITLE <u>Agent</u>	DATE <u>12/22/67</u>
APPROVED BY <u><i>[Signature]</i></u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY <u></u>		