

COUNTY ROOSEVELT		FIELD Chaveroo		STATE NM 30-041-00110	
OPR SHELL OIL CO.				MAP	
1 Shell-Brukenfeld					
Sec. 23, T-7-S, R-32-E				CO-ORD	
1980' FNL, 660' FEL of Sec.					
Spd 8-21-68					
Cnp 9-18-68		CLASS			
CRG & SX TUBING 3 5/8" 451' 4 1/2" 411'		FORMATION	DATUM	FORMATION	DATUM
EL RA IND HC A		TD 4680'			
TEMPORARILY ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

PROP DEPTH 4680' TYPE RT

9-1-68 F.R. 8-29-68
PD 4680' - SA
TD 4680', prep log.
Cored 4116-66', rec 50' being:
10' dolo., bldg wtr from vert fracs;
10' dolo., sli suc., tr. PPP, bldg oil & wtr;
4' dolo., NS;
18' dolo., sli suc., NS;
4' dolo., tight;
4' dolo., suc., tr. PPP, bldg oil & wtr.

8-3-68

Good.

Core 420'-437', res 50' being:

0' Solo., tight;

20' Solo., sucr., tight, PPP, bldg oil & wtr;

0' Solo., tight;

0' Solo., bldg oil & wtr.

Core 431a-466', res 50' being:

0' Anky;

11' Solo., bldg oil & wtr;

11' Solo., sucr., vuggy PPP, bldg oil;

2' Solo., tight;

13' Solo., sucr., tr. PPP, bldg oil.

TD 4680', PED 4647', testg.

Perf @ 4332', 4336', 4340', 4345', 4354',
4358', 4364', 4372', 4377', 4384' W/L SPE

Acid (4332-84') 6000 gals.

Solid & Plwd 10 EO + 184 BW in 36 hrs.

8-3-68

TD 4680', PED 4647', swbg.

Solid 15 BW w/tr. oil in 6 hrs (4332-84')

Plwd 4332-84' W/150 sx.

Perf @ 4329', 4334', 4338', 4338', 4344',
4354', 4360' W/1 SPE

Acid (4334-60') 2000 gals 280

Solid 75 BW + 67 BEW in 27 hrs (4334-60')

9-21-68

TD 4680', PED 4647', TEMPORARILY ABANDONED

Acid (4339-4360') 1250 gals.

Solid 5 BW (oil) in 3 hrs (4339-4360')

9-30-68

COMPLETION REQUESTED

LOG: Base Red Beds 1922', Yates 2170',

San Andres 3421', Pl Marker 3968', Yellowhorse

Zone 4218' (+243')