

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		6a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Drilling</b>		5. State Oil & Gas Lease No.
2. Name of Operator <b>Atlantic Richfield Company</b>		7. Unit Agreement Name
3. Address of Operator <b>P. O. Box 1978, Roswell, New Mexico 86201</b>		8. Farm or Lease Name <b>Tucker</b>
4. Location of Well UNIT LETTER <b>K</b> , <b>1880</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>West</b> LINE, SECTION <b>24</b> TOWNSHIP <b>7-S</b> RANGE <b>32-E</b> NMPM.		9. Well No. <b>3</b>
15. Elevation (Show whether DF, RT, GR, etc.)		10. Field and Pool, or Wildcat <b>Chaveroo-San Andres</b>
12. County <b>Roosevelt</b>		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	SUBSEQUENT REPORT OF:  REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.	

MI & RU Verna Drilling Company rotary tools. Spudded well @ 12:15 PM 9/14/68. Drld 12-1/4" hole to 390' SLM. Ran 12 jts 8-5/8" 8# 24#, J-55 ST&C Class II csg w/guide shoe & float collar = 372.48', set @ 381.83' RKB. Cemented w/250 sx Class "C" cement + 2% CaCl. Plug down @ 6:45 PM 9/14/68. Cement circulated. Ran 7-7/8" bit & tested 8-5/8" casing w/850# for 30 min. OK & job complete @ 2:30 PM 9/15/68 after 19 hrs WOC. Resumed drilling - 7-7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED O. D. Bretches TITLE Dist. Drlg. Supervisor DATE 9-27-68

APPROVED BY John W. Runyan TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: