

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 28 9 54 AM '69

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Thornton Lomax, Jr.	8. Farm or Lease Name DeLois Brannon
3. Address of Operator 4321 Republic National Bank Tower, Dallas, Texas 75201	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> , <u>682</u> FEET FROM THE <u>West</u> LINE AND <u>1980</u> FEET FROM THE <u>North</u> LINE, SECTION <u>31</u> TOWNSHIP <u>6S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4352 Gr.	12. County Roosevelt

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input checked="" type="checkbox"/>	OTHER	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 8-5/8" O.D. casing as follows:

10' to 2305' 2295' of 8-5/8" OD 24#/ft. J-55 ST&C
2305' to 4076' 1771' of 8-5/8" OD 32#/ft. J-55 ST&C
8-5/8" set at 4076' cemented with 100 sxs Incore Posmix and 150 sxs Halliburton Lite-weight all with 2% calcium chloride. Plug down @ 4:00 AM., 7/13/69. WOC 12 hrs., Tested casing to 1000 psi for 30 minutes. Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	TITLE <u>Agent</u>	DATE <u>July 22, 1969</u>
APPROVED BY <u>John W. Ramsey</u>	TITLE <u>Geologist</u>	DATE <u>JUL 28 1969</u>
CONDITIONS OF APPROVAL, IF ANY:		