



FOSTER TESTERS, INC.

TEST TICKET NO. 3629

ORDER NO. - - - -

DATE 8-8-72

COMPANY LEEDE & PINE

LEED STATE

WELL NO. 1

FIELD WILDCAT COUNTY ROOSEVELT STATE NEW MEXICO

TEST NO. 1

MAIL CHARTS TO AS DIRECTED

MAIL INVOICE TO LEEDE & PINE, 516 BLDG. OF SOUTHWEST, MIDLAND, TEXAS 79701

FORMATION TESTED TOTAL DEPTH 6772 MAIN HOLE 7-7/8" RAT HOLE - - - -
INTERVAL TESTED FROM 6462 TO 6472 Packer TYPE BT SIZE 6-5/8 NUMBER
DRILL PIPE SIZE 4 1/2" FH I.D. 3.8 COLLAR SIZE 4" H90 I.D. 2.25
TIME PACKER SET A.M. 2.23 P.M. PACKER SET 4 HRS. 15 MIN. PRE FLO TIME 15 MINS.
INITIAL FLOW MINS. 2ND FLOW 60 MINS. FINAL FLOW MINS.
INITIAL SHUT-IN MINS. 2ND SHUT-IN 120 MINS. FINAL SHUT-IN 2347 MINS.
RECORD TYPE AK-1 CAPACITY 5550-6600 NUMBER TOP BOTTOM
TOP RECORDER DEPTH 6768 BOTTOM RECORDER DEPTH 6772
MAX. TEMP. 160 TEMP. DEPTH 6769 CHOKE SIZE: TOP 1" ADJ. BOTTOM 5/8
MUD TYPE STARCH MUD WEIGHT 10 VISCOSITY 42 FILTER CAKE 2/32 WTR. LOSS 14.6
FLUID CUSHION TYPE - - - - AMOUNT - - - - REVERSED OUT YES NO X
CONVENTIONAL TEST X STRADDLE TEST YES CASING TEST YES MISS RUN
SECOND ASSEMBLY YES ROTARY JAR YES SAFETY JOINT YES
SAMPLER YES X NO FFE FLOW TOOL YES NO X CIRC. SUB YES NO X
SURFACE ACTION: RECEIVED VERY WEAK BLOW OF AIR FOR 15 MIN. INITIAL SHUT IN 60 MIN.
FINAL FLOW RECEIVED VERY WEAK BLOW FOR 45 MIN. FINAL SHUT IN 120 MIN.

Job separator sheet

RECOVERY: 285' DRLG. MUD

PIT SAMPLE CHLORIDES 105,000 P.P.M.

FLUID SAMPLER DATA: 100# PRESSURE NO GAS, NO OIL, NO WATER 2800 cc DRLG. MUD

REMARKS: STOPPING PRE FLOW TIME
600' TOTAL DC LEGNTH
MINUS 45' PENETRATION LEGNTH
M.M. 2800

HAROLD SCHMIDT

TEST APPROVED BY J.D. SWINEA

	RECORDER NO. 2755		RECORDER NO.		RECORDER NO.
INITIAL HYDROSTATIC PRESSURE	3646	P.S.I.		P.S.I.	P.S.I.
INITIAL SHUT IN PRESSURE	2213	P.S.I.	B-1	P.S.I.	P.S.I.
INITIAL FLOW PRESSURE	218-235	P.S.I.	C-1	P.S.I.	P.S.I.
FINAL FLOW PRESSURE	268-319	P.S.I.	D-1	P.S.I.	P.S.I.
FINAL SHUT IN PRESSURE	2179	P.S.I.		P.S.I.	P.S.I.
FINAL HYDROSTATIC PRESSURE	3646	P.S.I.		P.S.I.	P.S.I.

September 12, 1972

TO: New Mexico Oil Conservation Commission


SUBJECT: Deviation Record of the State No. 1, 660'/N,
660'/W, Sec. 16, T-1-S, R-31-E, Roosevelt
County, New Mexico

Operator: Leede & Pine

DEVIATION RECORD

300'	-	1/2 deg.
731'	-	1/4 deg.
1,085'	-	0
1,496'	-	3/4 deg.
1,887'	-	1 deg.
2,293'	-	3/4 deg.
2,454'	-	1 deg.
2,738'	-	3/4 deg.
3,061'	-	1 deg.
3,470'	-	1/2 deg.
3,842'	-	1/2 deg.
4,296'	-	1/2 deg.
4,510'	-	3/4 deg.
4,924'	-	1 deg.
5,051'	-	1/2 deg.
5,447'	-	1/2 deg.
5,668'	-	1/4 deg.
6,107'	-	1/4 deg.
6,264'	-	1/4 deg.
6,415'	-	1 deg.
6,510'	-	3/4 deg.
6,690'	-	3/4 deg.
6,770'	-	3/4 deg.
6,824'	-	3/4 deg.
6,997'	-	1/4 deg.
7,055'	-	1/4 deg.

TRI-SERVICE DRILLING COMPANY
Drilling Contractor


Weldon L. Dawson - Asst. Secretary