

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-600

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dual	7. Unit Agreement Name
2. Name of Operator Humble Oil & Refining Company	8. Farm or Lease Name New Mexico "CT" State
3. Address of Operator P. O. Box 1600, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER "C" 1,980 FEET FROM THE West LINE AND 660 FEET FROM THE North LINE, SECTION 15 TOWNSHIP 1-S RANGE 35-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Drilled 10-5/8" hole to 3,675', ran BH Acoustic Log, Laterlog and Sidewall Neutron Log. Ran 89 joints of 8-5/8" 28# 8R casing, set at 3,674'. Cemented with 1,500 sx Trinity Lite Weight cement w/3.75# salt per sx, followed w/200 sx Class "C" cement w/2% Calc. P. O. B. at 11:40 p.m. 9-2-72, circulated 420 sx cement. W. O. C. 18 hours. Tested B. O. P. and 8-5/8" casing to 2,000#, test O.K. Drilled cement from 3,635' to 3,675', now drilling ahead in 7-7/8" hole at 4,166' on 9-6-72.

Orig. & 2cc: NMOCC
cc: Andrews District
cc: Central File
cc: W. R. Wardroup
cc: D. L. Clemmer

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. L. Clemmer TITLE Proration Specialist DATE 9-6-72

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE SEP 11 1972

CONDITIONS OF APPROVAL, IF ANY: