

COUNTY <u>ROOSEVELT</u>		FIELD <u>Wildcat</u>		STATE <u>NM 30-041-20354</u>	
OPR <u>HUMBLE OIL & REFG. CO.</u>		MAP			
<u>1 New Mexico "CT" State</u>					
<u>Sec 15, T-1-S, R-35-E</u>					
CO-ORD					
<u>660' FNL, 1980' FWL of Sec</u>					
<u>Spd 8-20-72</u>					
<u>Cmp 10-16-72</u>		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
11 3/4" at 350' w/250 sx					
8 5/8" at 3674' w/1700 sx					
4 1/2" at 6974' w/300 sx					
LOGS EL GR RA IND HC A					
		TD 6974'			
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. <u>Delta</u>	PROP DEPTH <u>7900'</u>	TYPE <u>RT</u>
DATE		

F.R. 8-14-72; Opr's Elev. 4058' GL, 4071' DF
PD 7900' RT (Montoya)
Contractor - Delta

8-21-72	Drlg. 345'
8-28-72	Drlg. 1325'
9-5-72	Drlg. 3743'
9-11-72	Drlg. 4863'
9-18-72	Drlg. 6360'
9-25-72	Drlg. 6875'

DST 6755-6879', open 2 hrs 10 mins, rec 380'
GCDF + 380' DF, 30 min ISIP 1600#, FP 360-449#,
4 hr FSIP 1932#

10-2-72	TD 6974'; WO Comp
---------	-------------------

10-9-72

TD 6974'; PBD 6640'; Pulling 4 1/2" csg
Perf 6854-66'
Acid (6854-66') 2500 gals
Swbd & Flwd 41 BL&AW in 10 hrs (6854-66')
PB to 6830'
Perf @ 6652', 6669', 6721', 6729', 6741', 6756',
6777', 6787', 6801', 6807' w/1 SPI
Acid (6652-6807') 2500 gals
Swbd 51 BLW in 4 hrs (6652-6807')
PB to 6640'

10-16-72

TD 6794'; P&A (Hold for Tops)
Perf (San Andres) @ 3399', 3407', 3416', 3426',
3436', 3504', 3522', 3532', 3572', 3575', 3621',
3628' w/1 SPI

10-16-72

Continued
Acid (3399-3628') 2900 gals
Swbd 109 BLW, NS in 4 hrs (3399-3628')
Swbd 185 B sulf wtr in 10 hrs (3399-3436')

11-20-72

TD 6974'; PLUGGED & ABANDONED
LOG TOPS: San Andres 2500', Glorieta 3700',
Tubb 5065', Abo 5730', Wolfcamp 6342', Bough "C"
6638', Granite Wash 6860', Pre-Cambrian 6880'

11-25-72

COMPLETION REPORTED