

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name ---
2. Name of Operator Phillips Petroleum Company	8. Farm or Lease Name Wilcox-A
3. Address of Operator Room 711, Phillips Building, Odessa, Texas 79761	9. Well No. 1
4. Location of Well UNIT LETTER I 1980 FEET FROM THE south LINE AND 660 FEET FROM THE east LINE, SECTION 21 TOWNSHIP 5-S RANGE 30-E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) Later	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> Intermediate	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole f/360' to 3400', conditioned hole. Ran Schlumberger BHC. Integrated sonic GRC from 0'-3400'. Set 107 jts. (3400') 8-5/8" csg. at 3400', bottom to top as follows:

71 jts. (2240') 8-5/8" O.D., 32#, K-55, ST&C, A cond.
34 jts. (1100') 8-5/8" O.D., 24#, K-55, ST&C, A cond.
2 jts. (60') 8-5/8" O.D., 32#, K-55, ST&C, A cond.

Howco cemented w/300 ax Incor SR cmt., plug to 3366' w/1250#. Job complete 10:00 A.M., 11-14-72. WOC 18 hrs., tested csg w/1500# for 30 min., O.K. Ran temp. survey, TOC outside csg at 2380'. NU, started drilling ahead at 3400' w/7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Senior Reservoir Engr. DATE 11-15-72

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE NOV 17 1972
CONDITIONS OF APPROVAL, IF ANY: