

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY HOLE	7. Unit Agreement Name
2. Name of Operator McCLELLAN OIL CORPORATION	8. Farm or Lease Name MOC
3. Address of Operator Box 848, ROSWELL, NEW MEXICO	9. Well No. 1
4. Location of Well UNIT LETTER B, 660 FEET FROM THE NORTH LINE AND 1217 FEET FROM THE EAST LINE, SECTION 16, TOWNSHIP 6-S, RANGE 38-E, NMPM.	10. Field and Pool, or Wildcat WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.) 3928 GL 3941 DF	12. County ROOSEVELT

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK  PLUG AND ABANDON

TEMPORARILY ABANDON  CHANGE PLANS

PULL OR ALTER CASING  OTHER

SUBSEQUENT REPORT OF:

REMEDIAL WORK  ALTERING CASING

COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB

OTHER COMPLETION ATTEMPT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PLUG BACK TOTAL DEPTH IS 4280'. ON 4/24/73, PERFORATED 4 1/2" CASING AT 4210, 4211; 4212; 4218; 4220; 4222; 4225; 4227 & 4228. ACIDIZED WITH 2000 GALS. OF 15% ACID. SWABBED LOAD BACK, NO SHOW OF OIL OR GAS. SWABBED SULPHUR WATER. 800' IN HOLE. SET BRIDGE PLUG AT (WIRE LINE) 4190'. PERFORATED 4136, 38, 44, 46, 50, 52, 59, 69; 72 & 4174'. TREATED WITH 2000 GALS. 15% ACID. RECOVERED LOAD, WELL SWABBED DRY. VERY SLIGHT SHOW OF GAS, NO OIL OR WATER.

PROPOSE TO PLUG AS FOLLOWS

WILL PULL 4 1/2" CSG. AT FREE POINT AND SET 100' CEMENT IN AND OUT OF STUB. WILL ATTEMPT TO RE-COVER AS MUCH 8 5/8" AS POSSIBLE, AND WILL SET 100' CEMENT PLUG IN & OUT OF STUB. 12 3/4" WAS CIRCULATED, THEREFORE NONE OF THIS CASING WILL BE RECOVERED, BUT A 100' PLUG IN & OUT OF THE BASE OF THIS CASING (351') WILL BE RUN. A 10' PLUG AT THE SURFACE, AND A MARKER PLACED AT THE SURFACE. LOCATION WILL BE CLEANED, PITS COVERED IN AN ATTEMPT TO RE-STORE THE SURFACE AS NEAR AS POSSIBLE TO ITS ORIGINAL CONDITION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Joe L. McClellan TITLE PRESIDENT DATE 4/28/73

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: