

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Enserch Exploration, Inc.		8. Farm or Lease Name Lambirth
3. Address of Operator 7701 N. Stemmons Freeway, Suite 800, Dallas, Texas 75247		9. Well No. 1
4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 5S RANGE 33E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4413.8' (GR)		12. County Roosevelt

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 17-1/2" hole to 370'. Set 13-3/8", 48# new casing to 355'. Cemented with 350 sacks cement. Plug down April 2, 1978. Wait on cement 12 hours. Installed BOP's and tested casing to 1000 psi.

Drilled 12-1/4" hole to 3330'. Set 8-5/8", 32# & 24# new casing at 3327'. Cemented with 1950 sacks cement. Plug down April 21, 1978, circulated cement to surface. Wait on cement 12 hours. Installed BOP's tested casing to 1500 psi.

Drilled 7-7/8" hole to 7992'. Set 5-1/2", 15.5# new casing at 7961'. Cemented with 325 sacks cement. Opened stage tool at 4553' and cemented with 400 sacks cement. Plug down May 15, 1978.

Total depth 7992'. Logs attached.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J.R. Kunder* TITLE Drilling Superintendent DATE June 6, 1978

APPROVED BY John Runyan TITLE Geologist DATE JUN 09 1978
CONDITIONS OF APPROVAL, IF ANY