

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
9. Well No.	
10. Field and Pool, or Wildcat	
12. County	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	2. Name of Operator	3. Address of Operator	4. Location of Well	15. Elevation (Show whether DF, RT, GR, etc.)
Gas Producing Enterprises, Inc.		P.O. Box 235, Midland, Texas 79702		4311' GR
UNIT LETTER J		1980' FEET FROM THE South LINE AND 1980' FEET FROM THE East LINE, SECTION 34 TOWNSHIP 6-S RANGE 34-E NMPM.		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Gas Producing Enterprises, Inc. proposes to plug and abandon the Bessie Simpson Well No. 1 on July 9, 1978, as outlined below.

- Spot 50 sx. Class "C" cement plugs at 3440-3315', 2100-1975', 1000-870' and 520-350'.
- Spot 10 sx. Class "C" cement plug from 38' to surface.  
Clear location and install dry hole marker.

NOTE: All intervals not cemented will be filled with 9.6" mud. No casing recovery. Procedure verbally approved by Jerry Sexton 7-8-78.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Engineer DATE 7-11-78

APPROVED BY [Signature] TITLE District Engineer DATE 7-11-78

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 19 1978

CH. OBSERVATION COMM.  
HARRIS, H. M.