

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name	
2. Name of Operator Enserch Exploration, Inc.		8. Farm or Lease Name Lambirth	
3. Address of Operator P. O. Box 4815, Midland, Texas 79704		9. Well No. 6	
4. Location of Well UNIT LETTER <u>D</u> <u>766'</u> FEET FROM THE <u>West</u> LINE AND <u>766'</u> FEET FROM THE <u>North</u> LINE, SECTION <u>31</u> TOWNSHIP <u>5S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat South Peterson	
15. Elevation (Show whether DF, RT, GR, etc.) 4382.4' GR		12. County Roosevelt	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed from 4/9/83 to 4/16/83:

Set CIBP at 7600'.
Laid 5 sacks Class H cement from 7590' to 7555'.
Cut off 4-1/2" casing at 2000'.
Laid 60 sacks Class H cement from 2046' to 1860'.
Laid 15 sacks Class H cement from 30' to surface.
Cut off 8-5/8" casinghead, welded on 8-5/8" x 1/2" steel plate.
Installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. F. Burnett</u>	TITLE <u>Prod. Superintendent</u>	DATE <u>5/26/83</u>
APPROVED BY <u>David Catarock</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>JUL 14 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		