

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
39-041-20500

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
EP Operating Limited Partnership

3. Address of Operator
6 Desta Dr., Suite 5250, Midland, TX 79705-5510

4. Well Location
Unit Letter L : 1980 Feet From The South Line and 810 Feet From The West Line
Section 30 Township 5S Range 33E NMMPM Roosevelt County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4381.5' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/17/94: Ran Casing Inspection Log. Decision made to plug well.
9/19/94: Obtained verbal approval to plug well from Oil Conservation Division.
9/20/94: RIH to 7745'. Spotted 60 sack Class C cement plug. Waited 4 hrs. Tagged plug at 7494'. Circulated hole with 275 bbls. 10#/gal. gelled brine water.
9/21/94: Spotted 25 sx Class C cement at 4494'. Approximate top of plug at 4331'.
Spotted 25 sx Class C cement at 3166'. Approximate top of plug at 3003'.
Perforated 4 squeeze holes at 415'. Had full circulation down 7" casing and up 9-5/8" casing. Spotted 50 sx Class C cement. Waited 3 hrs. Tagged plug at 260'.
Cut off casinghead. Pumped 10 sack surface plug from 63' to surface. Welded on plate and dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE S. D. Reed TITLE Production Superintendent DATE 09/29/94

TYPE OR PRINT NAME S. D. Reed (915) 682-9756 TELEPHONE NO.

(This space for State Use)

APPROVED BY Billy E. Frutkin TITLE ✓ DATE

CONDITIONS OF APPROVAL, IF ANY: