

WELL IDENTIFICATION

COMPANY: ENSERCH EXPLORATION, INC.

WELL: LAMBRITH #8
TEST INTERVAL: 7793' TO 7838'
TEST NO: 2
COUNTY: ROOSEVELT
TECHNICIAN: ELLERMANN (HOBBS)

7706 NORTH STEMMONS FREEWAY
EMPIRE CENTRAL BLDG.: SUITE 800
DALLAS, TEXAS 75247
LOCATION: SEC. 30 - T5S - R33E
FIELD: WILD CAT
TEST DATE: 10-9-79
STATE: NEW MEXICO
TEST APPROVED BY: MR. LEO W. BLAKE

EQUIPMENT AND HOLE DATA

TEST TYPE:	M.F.E. OPEN HOLE	DRILL PIPE LENGTH:	7106	FT.
ELEVATION:	4397 K.B.	DRILL PIPE I.D.:	3.8	IN.
TOTAL DEPTH:	7838	DRILL COLLAR LENGTH:	651	FT.
MAIN HOLE/CASING SIZE:	8 3/4	DRILL COLLAR I.D.:	2.5	IN.
RAT HOLE/LINER SIZE:	-	PACKER DEPTHS:	7787 & 7793	FT.
FORMATION TESTED:	FUSSELMAN			FT.
NET PROD. INTERVAL:	30			FT.
POROSITY:	-	DEPTHS REF. TO:	KELLY BUSHING	FT.

TEST TOOL CHAMBER DATA

SAMPLER PRESSURE:	750	PSIG
RECOVERED OIL GRAVITY:	52.6 API @ 60 DEG. F.	
RECOVERY GOR:	498	FT3/BBL.
SAMPLE CHAMBER CONTENTS		
FLUID	VOLUME	MEAS. TEMP. (DEG F.)
GAS:	5.8 FT.3	CHLOR. (PPM)
OIL:	1850 CC	
WATER:	- CC	
MUD:	- CC	
FILTRATE:		
TOTAL LIQUID:	1850 CC	

MUD DATA

TYPE:	SALT WATER BASE
WEIGHT:	10.0 LB/GAL.
VISCOSITY:	40 SEC.
WATER LOSS:	12.8 CC
FLUID	RESIST (OHM-M) (DEG F) (PPM)
MUD:	TEMP
FILTRATE:	CHLOR
	60 128000

REMARKS

NO. OF REPORTS REQUESTED: 5 (3X)

FIELD REPORT NO. 19492D