

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. NM - 2579	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator MARATHON OIL COMPANY		8. Farm or Lease Name Luther Horton
3. Address of Operator P. O. Box 2409, Hobbs, New Mexico 88240		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>24</u> TOWNSHIP <u>3 - S</u> RANGE <u>32 - E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4323.3' GR		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Plan to set 100' cement plugs @ 1600 - 1700', 3660 - 3760', 5300 - 5400', 6700 - 6800', and 7600 - 7700'. Class "H" cement will be used for all plugs.
- 10 sacks of Class "H" cement will be placed at surface.
- Well will be capped with steel marker at least 4 inches in diameter set in cement with name and number of well clearly marked.
- The location will be cleared of all junk and the pits will be leveled when they are dried out.
- 312' of 13 3/8", 48# casing set @ 323' and 3695' of 9 5/8", 32#, 36#, and 40# casing set @ 3710' will be left in the hole. No casing will be pulled as both strings are cemented to surface.

THE COMMISSION MUST BE NOTIFIED
24 HOURS PRIOR TO COMMENCING WORK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael D. Anderson

TITLE Production Engineer

DATE August 22, 1979

Orig. Signed by
John Runyan
Geologist

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: