

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
NM-2579

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Marathon Oil Company	Luther Horton
3. Address of Operator	9. Well No.
P.O. Box 2409 Hobbs, NM 88240	1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM	Wildcat
THE East LINE, SECTION 24 TOWNSHIP 3-S RANGE 32-E N.M.P.M.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4323.3' GR	Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" surface hole at 11:45 p.m. CDT on 7-18-79. Drilled to 326'. Ran 8 joints 13 3/8", 48#, H-40, ST&C casing with float collar and guide shoe and set 11' below KDB to 323'. Cemented casing with 350 sacks Class "C" with 2% Calcium Chloride. Circulated 128 sacks to pit. Bumped plug with 900 psi. W.O.C. 24 hours. Nipped up BOP's. Tested casing to 600 psi. Held okay.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark E Brown TITLE Production Engineer DATE July 25, 1979

Orig. Signed by

Jerry Seneca

PROVED BY Jerry Seneca TITLE DATE JUL 27 1979

CONDITIONS OF APPROVAL, IF ANY, None